arXiv:1211.2627v1 [cs.CC] 12 Nov 2012

Computational Aspects of Nearly Single-Peaked Electorates*

Gábor Erdélyi
School of Economic Disciplines
University of Siegen
57076 Siegen, Germany

Martin Lackner and Andreas Pfandler
Institute of Information Systems
Vienna University of Technology
Vienna, Austria

November 12, 2012

Abstract

Manipulation, bribery, and control are well-studied ways of changing the outcome of an election. Many voting systems are in the general case computationally resistant to some of these manipulative actions. However when restricted to single-peaked electorates, these systems suddenly become easy to manipulate. Recently, Faliszewski, Hemaspaandra, and Hemaspaandra [FHH11] studied the complexity of dishonest behavior in nearly single-peaked electorates. These are electorates that are not single-peaked but close to it according to some distance measure.

In this paper we introduce several new distance measures regarding single-peakedness. We prove that determining whether a given profile is nearly single-peaked is in many cases NP-complete. Furthermore, we explore the relations between several notions of nearly single-peakedness and study the complexity of manipulation for nearly single-peaked elections.

1 Introduction

Voting is a very useful method for preference aggregation and collective decision-making. It has applications in very broad settings ranging from politics to artificial intelligence and further topics in computer science (see, e.g., [DKNS01, ER97, GMHS99]). In the presence of huge data volumes, the computational properties of voting rules are worth studying. In particular, we usually want to determine the winners of an election quickly. On the other hand we want to make various forms of dishonest behavior computationally hard.

Bartholdi, Tovey, and Trick [BTT89a] were the first to study the computational aspects of manipulation in elections, where a group of voters cast their votes insincerely in order to reach a desired outcome. Other types of dishonest behavior are control, where an external agent makes

---

[*] A preliminary version of this paper appeared in the proceedings of the *Fourth International Workshop on Computational Social Choice* [ELP12]. This work was done in part while the second and the third authors were visiting the University of Siegen and while the first author was visiting Vienna University of Technology. The work of the second and third author was supported by the Austrian Science Fund (FWF): P20704-N18. Author URLs: `http://www.uni-siegen.de/fb5/dt/team/erdelyi`, `http://www.dbai.tuwien.ac.at/staff/lackner/`, `http://www.dbai.tuwien.ac.at/staff/pfandler/`.

structural changes on the election such as adding/deleting/partitioning either candidates or voters (see, e.g., [BTT92]) in order to reach a desired outcome, or bribery, where an external agent changes some voters' votes in order to change the outcome of the election (see, e.g., [FHH09]). For an overview and many natural examples on bribery, control, and manipulation we refer to [BEH$^+$10, FHH10, FP10, BCE12].

Traditionally, the complexity of such attacks on the outcome is studied under the assumption that in each election any admissible vote can occur. However, there are many elections where the diversity of the votes is limited in a sense that there are some admissible votes nobody would ever cast. One of the best known examples is *single-peakedness*, introduced by Black [Bla48]. It assumes that the votes are polarized along some linear axis. The study of the computational aspects of elections with single-peaked preferences was initiated by Walsh [Wal07] (see also [FHHR11, BBHH10]). Many problems which are NP-hard in the general case turn out to be easy for single-peaked societies. A recent line of research initiated by Conitzer [Con09] and by Escoffier, Lang, and Öztürk [ELÖ08] suggests that many elections are not perfectly single-peaked but are *close* to it with respect to some metric. Faliszewski, Hemaspaandra, and Hemaspaandra [FHH11] introduced various notions of nearly single-peaked elections and showed that the complexity of manipulative actions jumps back to NP-hardness in many cases.

In this paper we consider the notion of *k*-maverick single-peakedness and *k*-local swaps introduced by Faliszewski, Hemaspaandra, and Hemaspaandra [FHH11]. In addition we follow the suggestions of Escoffier, Lang, and Öztürk [ELÖ08] and formally define the two nearly single-peaked notions *k*-candidate deletion and *k*-additional axes. Furthermore, we introduce three new notions of nearly single-peakedness, *k*-local candidate deletion, *k*-global swaps, and *k*-candidate partition. We show connections between the existing and new notions, and we study the complexity of determining whether a given profile is nearly single-peaked with respect to some axis. This problem was introduced by Escoffier, Lang, and Öztürk [ELÖ08] as *single-peaked consistency*. We show that single-peaked consistency is computationally hard for five notions of nearly single-peakedness given in this paper. Additionally, we present a polynomial time algorithm for *k*-candidate deletion. Finally, we study the complexity of manipulation of nearly single-peaked elections and are able to provide dichotomy theorems for each of the seven distance measures.

Related Work Our paper fits in the line of research on single-peaked and nearly single-peaked preferences. In the work of Ballester and Haeringer [BH11] a simple characterization of single-peaked elections has been found. This characterization does not depend on finding a suitable axis. Faliszewski et al. [FHHR11] and Brandt et al. [BBHH10] investigate the complexity of dishonest behavior (e.g., the complexity of manipulation and control) in electorates with single-peaked preferences as well as the winner problem. They do not consider nearly single-peaked preferences, but mention them as future work.

In the context of nearly single-peaked preferences the most relevant paper is by Faliszewski, Hemaspaandra, and Hemaspaandra [FHH11]. They introduce several notions of nearly single-peakedness and analyze the complexity of bribery, control, and manipulation under those conditions. In contrast, we are not only analyzing manipulation in elections, but we are studying the complexity of nearly single-peaked consistency. Additionally, we introduce new notions of nearly single-peakedness.

The question whether a given profile is single-peaked has been recently investigated by Escoffier, Lang, and Öztürk [ELÖ08]. The difference in their work is that they have not considered nearly single-peakedness, they only pointed it out as a possible future research direction.

The idea of measuring the distance of votes with the number of swaps required to make them identical already appears in Dodgson's voting rule (see, e.g., [MN08] for a discussion). This idea has been widely used since then. Elkind, Faliszewski, and Slinko used swaps of adjacent candidates in votes in the context of bribery [EFS09]. They assumed that a briber can perform a number of swaps in the votes in order to make his favorite candidate win the election. In our paper, we use swaps as a distance measure for nearly single-peakedness. We do not change the outcome of an election with swaps, we just measure the swap distance of a given profile to the nearest single-peaked profile. Two further distance measures have recently been studied. "Single-peaked width" has been been studied in the paper of Cornaz, Galand and Spanjaard [CGS12]. Elkind, Faliszewski, and Slinko [EFS12] define the *decloning* measure which describes the number of adjacent candidates (adjacent in every vote) that are merged into one candidate in order to obtain single-peakedness. For this measure they provide a polynomial time algorithm to check single-peaked consistency.

Finally, we remark that single-peaked preferences have been considered in the context of preference elicitation [Con09] and in the context of possible and necessary winners under uncertainty regarding the votes [Wal07].

Organization This paper is organized as follows. In Section 2, we recall some notions from voting theory and define single-peaked preferences. In Section 3, we introduce the problems we are investigating in our paper. Our results on the relations between the different notions of single-peakedness and on the complexity of single-peaked consistency are presented in Section 4. In Section 5 we discuss the complexity of manipulation in nearly single-peaked elections. Finally, Section 6 provides some conclusions and future directions.

2 Preliminaries

Let C be a finite set of *candidates*, V be a finite set of *voters*, and let $\succ$ be a *preference relation* (i.e., a tie-free and total order) over C. Without loss of generality let $V = \{1,\dots,n\}$. We call a candidate c the *peak* of a preference relation $\succ$ if $c \succ c_i$ for all $c_i \in C \setminus \{c\}$. Let $\mathscr{P} = (\succ_1,\dots,\succ_n)$ be a *preference profile* (i.e., a collection of linear orders) over the candidate set C. We say that the preference order $\succ_i$ is the *vote* of voter i. For simplicity, we will write for each voter $i \in V$ $c_1c_2\dots c_m$ instead of $c_1 \succ_i c_2 \succ_i \dots \succ_i c_m$. For a vote $\succ_i = c_1c_2\dots c_m$ let the vote $\overline{\succ_i} = c_mc_{m-1}\dots c_1$ denote $\succ_i$'s *reverse* vote. We call the peak of voter i his highest ranked or *top-ranked* candidate. For two preference profiles over the same set of candidates $\mathscr{P} = (\succ_1,\dots,\succ_n)$ and $\mathscr{L} = (\succ_{n+1},\dots,\succ_s)$, let $(\mathscr{P},\mathscr{L}) = (\succ_1,\dots,\succ_s)$ define the *union* of the two preference profiles. In our constructions, we sometimes also insert a subset of the candidates $B \subseteq C$ into a vote, where we assume some arbitrary, fixed order of the candidates in B (e.g., c_1Bc_3 means that c_1 is the top-ranked candidate and c_3 is the last ranked candidate, while all $b \in B$ are ranked between c_1 and c_3). An *election* is defined as a triple $E = (C,V,\mathscr{P})$, where C is the set of candidates, V the set of voters and $\mathscr{P}$ a preference profile over C.

A *voting correspondence* $\mathscr{F}$ is a mapping from a given election $E = (C,V,\mathscr{P})$ to a non-empty subset $W \subseteq C$; we call the candidates in W the *winners* of the election E. A special case of a voting correspondence is a *voting rule*, where for any election E, $|\mathscr{F}(E)| = 1$. We will sometimes abuse terminology and refer to voting correspondences as voting rules.

A prominent class of voting rules is the class of scoring rules. Given a *scoring vector* $\alpha = (\alpha_1, \dots, \alpha_k)$, $\alpha_i \in \mathbb{N}$, $\alpha_1 \geq \cdots \geq \alpha_k$. In a *k-candidate scoring rule* each voter has to specify a tie-free linear ordering of all candidates and gives α_i points to the candidate ranked on position i. The winners of the election are the candidates with the highest overall score. *Veto* is the scoring rule defined by the scoring vector $\alpha = (1, \dots, 1, 0)$.

In order to define single-peaked profiles we will make use of the definition given by Escoffier et al. [ELÖ08].

Definition 2.1 ([ELÖ08])**.** *Let an* axis *A be a total order over C denoted by $>$. Given two candidates $c_i, c_j \in C$, a vote $k \in V$ specified by the corresponding preference relation $\succ_k$, and an axis A. Let c be the top-ranked candidate of voter k. We say that candidates c_i and c_j are* on the same side of the peak of $\succ_k$ *if one of the following two conditions holds:*

$$\text{(1)} \quad c_i > c \text{ and } c_j > c, \text{ or} \qquad\qquad \text{(2)} \quad c > c_i \text{ and } c > c_j$$

A vote k is said to be single-peaked with respect to an axis *A if for all $c_i, c_j \in C$ that are on the same side of the peak c of $\succ_k$ it holds that $c_i \succ_k c_j$ if either $c > c_i > c_j$ or $c_j > c_i > c$ holds (i.e., c_i is closer to the peak than c_j).*

A preference profile $\mathscr{P}$ is said to be single-peaked with respect to an axis *A if and only if each vote is single-peaked with respect to A. A preference profile $\mathscr{P}$ is said to be* single-peaked consistent *if there is an axis A such that $\mathscr{P}$ is single-peaked with respect to A.*

Analogously to reverse votes, the to axis A reverse axis will be denoted by $\overline{A}$. Let $C' \subseteq C$. By $\mathscr{P}[C']$ we denote the profile $\mathscr{P}$ restricted to the candidates in C'. Analogously if A is an axis over C, we denote by $A[C']$ the axis A restricted to candidates in C'.

Escoffier, Lang, and Öztürk present an algorithm that decides whether a given preference profile is single-peaked consistent in time $|V| \cdot |C|$ [ELÖ08]. Their algorithm improves upon the runtime of an algorithm presented in [BT86]. The corresponding decision problem is defined as follows.

SINGLE-PEAKED CONSISTENCY	
Given:	An election $E = (C, V, \mathscr{P})$.
Question:	Is $\mathscr{P}$ single-peaked consistent?

3 Problem Statement

In this paper we consider different notions of nearly single-peakedness. All these notions define a distance measure to single-peaked profiles. We will now describe them and provide first (trivial) upper bounds on these distances.

k-Maverick

The first formal definition of nearly single-peaked societies was given by Faliszewski, Hemaspaandra, and Hemaspaandra [FHH11]. Consider a preference profile $\mathscr{P}$ for which most voters are single-peaked with respect to some axis A. All voters that are not single-peaked with respect to A are called mavericks. The number of mavericks defines a natural distance measure to single-peakedness. If an axis can be found for a large subset of the voters, this is still a fundamental observation about the structure of the votes.

Definition 3.1 ([FHH11])**.** *Let $E = (C,V,\mathscr{P})$ be an election and k a positive integer. We say that the profile $\mathscr{P}$ is k-*maverick single-peaked consistent *if by removing at most k preference relations (votes) from $\mathscr{P}$ one can obtain a preference profile $\mathscr{P}'$ that is single-peaked consistent.*

Let $M(\mathscr{P})$ denote the smallest k such that $\mathscr{P}$ is k-maverick single-peaked consistent. Note that $M(\mathscr{P}) \leq |V| - 1$ always holds.

The above notion is a well-motivated distance regarding single-peakedness, but we will define other distances which could be more useful in other cases.

k-Candidate Deletion

As suggested in [ELÖ08], we introduce outlier candidates. These are candidates that do not have "a correct place" on any axis and consequently have to be deleted in order to obtain a single-peaked consistent profile. Examples could be a candidate that is not well-known (e.g., a new political party) or a candidate that prioritizes other topics than most candidates and thereby is judged by the voters according to different criteria. The votes restricted to the remaining candidates might still have a clear and significant structure, i.e., might be single-peaked consistent.

Definition 3.2. *Let $E = (C,V,\mathscr{P})$ be an election and k a positive integer. We say that the profile $\mathscr{P}$ is k-*candidate deletion single-peaked consistent *if we can obtain a set $C' \subseteq C$ by removing at most k candidates from C such that the preference profile $\mathscr{P}[C']$ is single-peaked consistent.*

Let $CD(\mathscr{P})$ denote the smallest k such that $\mathscr{P}$ is k-candidate deletion single-peaked consistent. Note that $CD(\mathscr{P}) \leq |C| - 2$ always holds.

k-Local Candidate Deletion

Personal friendships or hatreds between voters and candidates could move candidates up or down in a vote. These personal relationships cannot be reflected in a global axis. To eliminate the influence of personal relationships to some candidates we define a local version of the previous notion. This notion can also deal with the possibility that the least favorite candidates might be ranked without special consideration or even randomly.

We first have to define partial domains and partial profiles.

Definition 3.3. *Let C be a set of candidates and A an axis over C. A preference relation $\succ$ over a candidate set $C' \subset C$ is called a partial vote. It is said to be* single-peaked with respect to A *if it is single-peaked with respect to $A[C']$. A partial preference profile consists of partial votes. It is called* single-peaked consistent *if there exists an axis A such that its partial votes are single-peaked with respect to A.*

Definition 3.4. *Let $E = (C,V,\mathscr{P})$ be an election and k a positive integer. We say that the profile $\mathscr{P}$ is k-*local candidate deletion single-peaked consistent *if by removing at most k candidates from each vote in $\mathscr{P}$ we obtain a partial preference profile $\mathscr{P}'$ that is single-peaked consistent.*

Let $LCD(\mathscr{P})$ denote the smallest k such that $\mathscr{P}$ is k-local candidate deletion single-peaked consistent. Note that $LCD(\mathscr{P}) \leq |C| - 2$ always holds.

k-Additional Axes

Another suggestion in [ELÖ08] is to consider the minimum number of axes such that each preference relation of the profile is single-peaked with respect to at least one of these axes. This notion is particularly useful if each candidate represents opinions on several issues (as it is the case in political elections). A voter's ranking of the candidates would then depend on which issue is considered most important by the voter and consequently each issue might give rise to its own corresponding axis.

Definition 3.5. *Let $E = (C, V, \mathscr{P})$ be an election and k a positive integer. We say that the profile $\mathscr{P}$ is k-*additional axes single-peaked consistent *if there is a partition $V_1, \dots, V_{k+1}$ of V such that the corresponding preference profiles $\mathscr{P}_1, \dots, \mathscr{P}_{k+1}$ are single-peaked consistent.*

Let $AA(\mathscr{P})$ denote the smallest k such that $\mathscr{P}$ is k-additional axes single-peaked consistent. Note that $AA(\mathscr{P}) < \min\left(|V|, \frac{|C|!}{2}\right)$ always holds. This is because the number of distinct votes is trivially bounded by $|V|$. Furthermore, $AA(\mathscr{P})$ is bounded by $\frac{|C|!}{2}$ since at most $|C|!$ distinct votes exist and each vote and its reverse are single-peaked with respect to the same axes.

k-Global Swaps

There is a second method of dealing with candidates that are "not placed correctly" according to an axis A. Instead of deleting them from either the candidate set C or from a vote, we could try to move them to the right position. We do this by performing a sequence of swaps of consecutive candidates. We remark the minimum number of swaps required to change one vote to another is the *Kendall distance* of these two votes (permutations). For example, to get from vote *abcd* to vote *adbc*, we first have to swap candidates c and d, and then we have to swap b and d. Since this changes the votes in a more subtle way, this can be considered a less obtrusive notion than k-(Local) Candidate Deletion.

Definition 3.6. *Let $E = (C, V, \mathscr{P})$ be an election and k a positive integer. We say that the profile $\mathscr{P}$ is k-*global swaps single-peaked consistent *if $\mathscr{P}$ can be made single-peaked by performing at most k swaps in the profile. (Note that these swaps can be performed wherever we want – we can have k swaps in only one vote, or one swap each in k votes.)*

Let $GS(\mathscr{P})$ denote the smallest k such that $\mathscr{P}$ is k-global swaps single-peaked consistent. Note that $GS(\mathscr{P}) \leq \binom{|C|}{2} \cdot |V|$ always holds since rearranging a total order in order to obtain any other total order requires at most $\binom{|C|}{2}$ swaps.

k-Local Swaps

We can also consider a "local budget" for swaps, i.e., we allow up to k swaps per vote. This distance measure has been introduced in [FHH11] as Dodgson$_k$.

Definition 3.7. *Let $E = (C, V, \mathscr{P})$ be an election and k a positive integer. We say that the profile $\mathscr{P}$ is k-*local swaps single-peaked consistent *if $\mathscr{P}$ can be made single-peaked consistent by performing no more than k swaps per vote.*

Let $LS(\mathscr{P})$ denote the smallest k such that $\mathscr{P}$ is k-local swaps single-peaked consistent. Note that $LS(\mathscr{P}) \leq \binom{|C|}{2}$ always holds.

k-Candidate Partition

Our last nearly single-peaked formalism is the candidate analogon of k-additional axes. In this case we partition the set of candidates into subsets such that all of the restricted profiles are single-peaked consistent. This notion is useful in the following situation. Each candidate has an opinion on a controversial Yes/No-issue. Depending on their own preference voters will always rank all Yes-candidates before or after all No-candidates. It might be that when considering only the Yes- respectively No-candidates, the election is single-peaked. Therefore, if we acknowledge the importance of this Yes/No-issue and partition the candidates accordingly, we may obtain two single-peaked elections.

Definition 3.8. *Let $E = (C, V, \mathscr{P})$ be an election and k a positive integer. We say that the profile $\mathscr{P}$ is* k-candidate partition single-peaked consistent *if the set of candidates C can be partitioned into at most k disjoint sets $C_1, \ldots, C_k$ with $C_1 \cup \ldots \cup C_k = C$ such that the profiles $\mathscr{P}[C_1], \ldots, \mathscr{P}[C_k]$ are single-peaked consistent.*

Let $CP(\mathscr{P})$ denote the smallest k such that $\mathscr{P}$ is k-candidate partition single-peaked consistent. Note that $CP(\mathscr{P}) \leq \left\lceil \frac{|C|}{2} \right\rceil$ always holds.

Decision Problems

We now introduce the seven problems we will study. We define the following problem for X $\in$ {Maverick, Candidate Deletion, Local Candidate Deletion, Additional Axes, Global Swaps, Local Swaps, Candidate Partition}.

X SINGLE-PEAKED CONSISTENCY	
Given:	An election $E = (C, V, \mathscr{P})$ and a positive integer k.
Question:	Is $\mathscr{P}$ k-X single-peaked consistent?

In Section 5 we investigate the complexity of coalitional manipulation in scoring rules under the assumption that the underlying elections are nearly single-peaked. For that we have to formally define the coalitional weighted manipulation problem for nearly single-peaked electorates first.

$\mathscr{F}$-X-CONSTRUCTIVE COALITIONAL WEIGHTED MANIPULATION ($\mathscr{F}$-X-CCWM)	
Given:	An integer k, a set of candidates C, a set of nonmanipulative voters V specified by weights and the preference profile $\mathscr{P} = (P_1, \ldots, P_h)$, where $\lvert V \rvert = h$, a set of manipulative voters S with $\lvert S \rvert = s$ with their weights $k_1, \ldots, k_s$, an axis[1] A over C, and a (preferred) candidate $p \in C$.
Question:	Is there a preference profile $\mathscr{L} = (L_1, \ldots, L_s)$ for the manipulative voters in S such that p is the unique winner in $(C, V \cup S, (\mathscr{P}, \mathscr{L}))$ with respect to the voting correspondence $\mathscr{F}$ and that $(\mathscr{P}, \mathscr{L})$ is k-X single-peaked consistent with respect to axis A?

If we fix the integer k to a constant ℓ, we denote this problem as $\mathscr{F}$-ℓ-X-Constructive Coalitional Weighted Manipulation ($\mathscr{F}$-ℓ-X-CCWM).

---

[1] For $\mathscr{F}$-ADDITIONAL AXES-CCWM we require that all axes are part of the input.

4 Results

4.1 Basic Results about Single-Peaked Profiles

We start with a simple observation which we will use in several proofs.

Lemma 4.1. *Let* $\mathscr{P}$ *be a preference profile containing the preference relation* $\succ$: $c_1 \dots c_m$ *and its reverse* $\overline{\succ}$. *Then* $\mathscr{P}$ *is either single-peaked with respect to the axis* $c_1 < \dots < c_m$ *(and its reverse) or it is not single-peaked at all.*

Proof. Since the vote $\succ$ ranks c_m last while the vote $\overline{\succ}$ ranks c_1 last, these candidates have to be at the left-most and right-most position on any compatible axis. Note that c_1 is the peak in $\succ$. Hence this already determines the position of all other candidates. Consequently only two axes are possible: $c_1 < \dots < c_m$ and $c_m < \dots < c_1$. ❑

Lemma 4.2 provides an alternative characterization of single-peaked consistency.

Lemma 4.2. *Given an election* $(C,V,\mathscr{P})$*, the profile* $\mathscr{P}$ *is not single-peaked consistent if and only if for all axes* A *there is some voter* $v \in V$ *and three candidates* $c_i, c_j, c_k \in C$ *such that* $c_i > c_j > c_k$ *on axis* A*, and* $c_i \succ_v c_j$ *holds as well as* $c_k \succ_v c_j$.

Proof. Assume that $\mathscr{P}$ is not single-peaked consistent. Then, for each axis A, there has to exist some voter v that is not single-peaked with respect to A. Let c be the top-ranked candidate of voter v. Then there exist some $c_1, c_2 \in C$ with either $c > c_1 > c_2$ or $c < c_1 < c_2$ such that $c_2 \succ c_1$. Depending on whether $c > c_1 > c_2$ or $c < c_1 < c_2$ we can instantiate (c_i, c_j, c_k) with either (c, c_1, c_2) or with (c_1, c_2, c). It is now easy to see that $c_i > c_j > c_k$, $c_i \succ_v c_j$ and $c_k \succ_v c_j$.

Let A be an axis over C. For the converse direction assume that there is some voter v and three candidates $c_i, c_j, c_k \in C$ such that $c_i > c_j > c_k$ on axis A, $c_i \succ_v c_j$ and $c_k \succ_v c_j$. Notice that c_j cannot be the peak of voter v since then $c_i \succ_v c_j$ and $c_k \succ_v c_j$ would not be true. Consequently the peak c is either smaller or larger than c_j with respect to A. We consider only the first case – the other case can be dealt with analogously. It holds that $c < c_j < c_i$. Furthermore, it holds that $c \succ_v c_i \succ_v c_j$. Therefore is $\mathscr{P}$ not single-peaked consistent. ❑

The following observation says that any subelection, i.e., an election with the same voters over a subset of the candidate set, of a single-peaked election is also single-peaked.

Lemma 4.3. *Let* $(C,V,\mathscr{P})$ *be a given election and* $C' \subseteq C$. *If* $\mathscr{P}$ *is single-peaked consistent then also* $\mathscr{P}[C']$ *is single-peaked consistent.*

Proof. Assume towards a contradiction that there is some $C' \subseteq C$ such that $\mathscr{P}[C']$ is not single-peaked consistent. Let A be an arbitrary axis ordering C. By Lemma 4.2 there is some voter $v \in V$ and three candidates $c_i, c_j, c_k \in C'$ such that $c_i > c_j > c_k$ on the axis $A[C']$, $c_i \succ_v c_j$ and $c_k \succ_v c_j$. Then, however, it also holds that $c_i > c_j > c_k$ on the axis A since A is an extension of $A[C']$. Therefore the right-hand side of Lemma 4.2 holds for every axis A over C. Hence, by Lemma 4.2, $\mathscr{P}$ is not single-peaked consistent. ❑



GS . . . Global Swaps
M . . . Maverick
CD . . . Candidate Deletion
LS . . . Local Swaps
AA . . . Additional Axes
CP . . . Candidate Partition
LCD . . . Local Candidate Deletion

Figure 1: Hasse diagram of the partial order described in Theorem 4.4.

4.2 Relations between Notions of Nearly Single-Peakedness

Theorem 4.4 shows several inequalities that hold for the distance measures under consideration. We hereby show how these measures relate to each other. Notice that these inequalities do not have an immediate impact on a classical complexity analysis such as in Section 4.3. However, they turn to out to be very useful for the complexity analysis of manipulation in nearly single-peaked elections.

Theorem 4.4. *Let $\mathscr{P}$ be a preference profile. Then the following inequalities hold:*

(1) $LS(\mathscr{P}) \leq GS(\mathscr{P})$.

(2) $LCD(\mathscr{P}) \leq CD(\mathscr{P})$.

(3) $CD(\mathscr{P}) \leq GS(\mathscr{P})$.

(4) $LCD(\mathscr{P}) \leq LS(\mathscr{P})$.

(5) $M(\mathscr{P}) \leq GS(\mathscr{P})$.

(6) $AA(\mathscr{P}) \leq M(\mathscr{P})$.

(7) $CP(\mathscr{P}) \leq CD(\mathscr{P}) + 1$.

(8) $CP(\mathscr{P}) \leq LS(\mathscr{P}) + 1$.

This list is complete in the following sense: Inequalities that are not listed here and that do not follow from transitivity do not hold in general. The resulting partial order with respect to $\leq$ is displayed in Figure 1 as a Hasse diagram.

Proof. Inequalities 1 and 2 are immediate consequences from the definitions since k-LS allows more swaps than k-GS and k-LCD allows more candidate deletions than k-CD. Inequalities 3 and 4 are due to the fact that swapping two candidates in a vote is at most as effective as removing one of these candidates. Similarly, for Inequality 5 observe that removing the corresponding voter is at least as effective as swapping two candidates in the vote. Concerning Inequality 6 observe that instead of deleting a voter we can always add an additional axis for this voter. Inequality 7 follows from the fact that putting each deleted candidate in its own partition leads to single-peakedness if deleting these candidates does.

In order to show Inequality 8 let $\mathscr{P}$ be k-local swaps single-peaked consistent. This means that there exists an axis A such that after performing at most k swaps per voter, $\mathscr{P}$ becomes single-peaked with respect to A. Without loss of generality assume that the axis A is $c_1 < c_2 < \ldots < c_n$. We now partition the candidates in $k+1$ sets $S_0, \ldots, S_k$. This is done by putting the i-th smallest element of A into the (i modulo $k+1$)-th set. Since we assume that A is $c_1 < c_2 < \ldots < c_n$, we can equivalently say that c_i is put into the (i modulo $k+1$)-th set, i.e., the c_1 in S_1, the c_2 in S_2, the c_k in S_k and c_{k+1} in S_0. Let $S \in \{S_0, \ldots, S_k\}$. Towards a contradiction assume that $\mathscr{P}[S]$ is not single-peaked with respect to $A[S]$. By Lemma 4.2 there exists some voter $v \in V$ and three candidates $c_i, c_j, c_k \in C$ such that $c_i < c_j < c_k$ on axis $A[S]$ (or equivalently $i < j < k$), $c_i \succ_v c_j$ and $c_k \succ_v c_j$. On axis A the distance between c_i and c_j respectively c_j and c_k is at least $k+1$, i.e.,

	M($\mathscr{P}$)	CD($\mathscr{P}$)	LCD($\mathscr{P}$)	GS($\mathscr{P}$)	LS($\mathscr{P}$)	AA($\mathscr{P}$)	CP($\mathscr{P}$)
Maverick .... M($\mathscr{P}$)	=	1	4	$\leq$	4	1	1
Candidate Deletion .... CD($\mathscr{P}$)	3	=	4	$\leq$	4	3	3
Local Candidate Deletion ... LCD($\mathscr{P}$)	3	$\leq$	=	$\leq$	$\leq$	3	3
Global Swaps .... GS($\mathscr{P}$)	2	2	2	=	4	2	2
Local Swaps................. LS($\mathscr{P}$)	2	2	2	$\leq$	=	2	2
Additional Axes............. AA($\mathscr{P}$)	$\leq$	5	5	$\leq$	6	=	5
Candidate Partition .... CP($\mathscr{P}$)	8	$\leq$	7	$\leq$	$\leq$	8	=

Table 1: Inequalities regarding the distance measures. This table should be read as follows. Measures on the left-most column are bounded ($\leq$) by the measures in the top row. Numbers point to the corresponding counterexamples if no such bound exists.

at least k elements lie in between them. We know that at most k swaps in $\succ_v$ can make this vote single-peaked with respect to A. Let $\succ'_v$ denote this swapped vote. Necessarily these swaps have to either cause that $c_j \succ'_v c_{j-1} \succ'_v \ldots \succ'_v c_{i+1} \succ'_v c_i$ holds or that $c_j \succ'_v c_{j+1} \succ'_v \ldots \succ'_v c_{k-1} \succ'_v c_k$ holds in $\succ'_v$ (depending whether the peak of $\succ'_v$ is right or left of c_j). Let us focus on the case that the swaps ensure that $c_j \succ'_v c_{j-1} \succ'_v \ldots \succ'_v c_{i+1} \succ'_v c_i$ – the other case is analogous. For $\succ_v$, contrary to $\succ'_v$, it holds that $c_i \succ_v c_j$. Hence these swaps have to cause that $c_j \succ'_v c_i$ holds. In addition, at least k elements, namely $c_{i+1}, \ldots, c_{j-1}$, have to be in between them. This requires at least $k+1$ swaps which contradicts the fact that at most k swaps suffice. Therefore for all partition sets S, $\mathscr{P}[S]$ is single-peaked consistent and $CP(\mathscr{P}) \leq LS(\mathscr{P}) + 1$.

It remains to show that these are indeed all inequalities. This can be done by providing counterexamples for each remaining case.

Table 1 offers an overview by pointing to the corresponding counterexample. In the following examples we assume that $n \geq 4$.

Counterexample 1 (M cannot be bounded by CD, AA and CP): Consider the preference profile over the candidate set $C = \{c_1, \ldots, c_n\}$ with the following $2n$ voters:

- There are n voters of the form: $c_1 \; c_2 \; \ldots \; c_n$.
- There are n voters of the form: $c_n \; c_2 \; c_3 \; \ldots \; c_{n-1} \; c_1$.

The corresponding preference profile $\mathscr{P}$ is not single-peaked consistent. This is because c_2 has to be next to both c_1 and c_n on any suitable axis but both have to be either the left-most or right-most element. Consequently, $M(\mathscr{P}) = n$. Removing candidates instead of voters is far more useful in this case. When we remove either c_1 or c_n, $\mathscr{P}$ becomes single-peaked and hence $CD(\mathscr{P}) = 1$. Since we have only two distinct votes, we require two axes to make $\mathscr{P}$ single-peaked and hence $AA(\mathscr{P}) = 1$. Furthermore, notice that we can obtain single-peaked consistency by partitioning the candidates into two sets $C_1 = \{c_1, c_n\}$ and $C_1 = \{c_2, \ldots, c_{n-1}\}$. As a consequence $CP(\mathscr{P}) = 2$.

Counterexample 2 (Neither GS nor LS can be bounded by AA, CD, LCD and CP): This counterexample is similar to the previous one but $\mathscr{P}$ consists of only two votes. Let $C = \{c_1, \ldots, c_{3n+1}\}$ be the set of candidates.

- There is one voter of the form: $c_1 \ c_2 \ \dots \ c_{3n+1}$.
- There is one voter of the form: $c_{3n+1} \ c_2 \ c_3 \ \dots \ c_{3n} \ c_1$.

If we consider this profile $\mathscr{P}$ restricted to the candidates c_1, c_{n+1}, c_{2n+1} and c_{3n+1}, i.e., $\mathscr{P}[\{c_1, c_{n+1}, c_{2n+1}, c_{3n+1}\}]$, we observe that this restricted profile is not single-peaked. Consequently, by Lemma 4.3, $\mathscr{P}$ is not single-peaked as well. If we want to make $\mathscr{P}$ single-peaked with swaps, at least two of $\{c_1, c_{n+1}, c_{2n+1}, c_{3n+1}\}$ have to swap position. This requires at least n swaps and consequently $GS(\mathscr{P}) \geq LS(\mathscr{P}) \geq n$. Since there are only two voters, $AA(\mathscr{P}) = M(\mathscr{P}) = 1$. As in the previous counterexample removing either c_1 or c_{3n+1} yields a single-peaked profile and hence $CD(\mathscr{P}) = 1$. Since $CP(\mathscr{P}) \leq CD(\mathscr{P})$ also $CP(\mathscr{P}) = 1$. Finally, $LCD(\mathscr{P}) \leq CD(\mathscr{P})$ implies $LCD(\mathscr{P}) = 1$.

Counterexample 3 (Neither CD nor LCD can be bounded by M, AA and CP): This time we consider three votes over the candidates $C = \{c_1, \dots, c_{2n}\}$.

- There is one voter $\succ_1$ of the form: $c_1 \ c_2 \ \dots \ c_{2n}$.
- There is one voter $\succ_2$ of the form: $c_{2n} \ c_{2n-1} \ \dots \ c_1$.
- There is one voter $\succ_3$ of the form: $c_n \ \dots \ c_1 \ c_{n+1} \ \dots \ c_{2n}$.

By Lemma 4.1 we only have to consider the axis $c_1 < c_2 < \dots < c_{2n}$ for $\mathscr{P} = (\succ_1, \succ_2, \succ_3)$. The third vote $\succ_3$ is however not single-peaked with respect to this axis. Hence $\mathscr{P}$ is not single-peaked consistent. Here $M(\mathscr{P}) = 1$ since deleting voter $\succ_3$ leads to single-peaked consistency. Since $AA(\mathscr{P}) \leq M(\mathscr{P})$ also $AA(\mathscr{P}) = 1$. However, we need to remove by far more candidates. We have to remove candidates such that the indices of the remaining candidates in $\succ_3$ are either increasing or decreasing. That are at least $n-1$ and hence $CD(\mathscr{P}) \geq LCD(\mathscr{P}) \geq n-1$. Finally, we have that $\mathrm{CP}(\mathscr{P}) = 2$ since $\mathscr{P}[\{c_1, \dots, c_n\}]$ and $\mathscr{P}[\{c_{n+1}, \dots, c_{2n}\}]$ are single-peaked consistent.

Counterexample 4 (Neither M, GS nor CD can be bounded by LCD and LS): We consider an election with $3n$ votes over the candidates $C = \{c_1, \dots, c_{3n}\}$.

- There are n voters $\succ_1, \dots, \succ_n$ of the form: $c_1 \ c_2 \ \dots \ c_{3n}$.
- There are n voters $\succ_{n+1}, \dots, \succ_{2n}$ of the form: $c_{3n} \ c_{3n-1} \ \dots \ c_1$.
- The remaining votes are obtained from the first vote by swapping the first two candidates in each block consisting of three candidates. Formally, for each i, $1 \leq i \leq n$ there is a voter $\succ_{2n+i}$ of the form: $c_1 \ \dots \ c_{3(i-1)} \ c_{3(i-1)+2} \ c_{3(i-1)+1} \ c_{3i} \ \dots \ c_{3n}$.

Let $\mathscr{P} = (\succ_1, \succ_2, \dots, \succ_{3n})$. By using Lemma 4.1 it is easy to check that for each $1 \leq i \leq n$, $\mathscr{P}[\{c_{3(i-1)+2}, c_{3(i-1)+1}, c_{3i}\}]$ is not single-peaked consistent. By Lemma 4.3, $\mathscr{P}$ is not single-peaked consistent. Also, this implies that we have to remove at least one candidate in each set $\{c_{3(i-1)+2}, c_{3(i-1)+1}, c_{3i}\}$ in order to make $\mathscr{P}$ single-peaked consistent. Therefore $CD(\mathscr{P}) \geq n$. Since $GS(\mathscr{P}) \geq CD(\mathscr{P})$ also $GS(\mathscr{P}) \geq n$. We now want to prove a lower bound on $M(\mathscr{P})$. If we delete $n-1$ voters then at least one vote of $\{\succ_1, \dots, \succ_n\}$, one of $\{\succ_{n+1}, \dots, \succ_{2n}\}$ and one of $\{\succ_{2n+1}, \dots, \succ_{3n}\}$ remains. Again by Lemma 4.3, $\mathscr{P}$ is not single-peaked consistent. Hence

$M(\mathscr{P}) > n-1$. Finally, notice that the votes $\succ_{2n+1}, \ldots, \succ_{3n}$ can be turned into vote $\succ_1$ by a single swap, which shows that $LS(\mathscr{P}) = 1$. Since $LCD(\mathscr{P}) \leq LS(\mathscr{P})$ also $LCD(\mathscr{P}) = 1$.

Counterexample 5 (AA cannot be bounded by CD, LCD and CP): In this example we use n votes over the candidates $C = \{c_1, \ldots, c_{n+1}\}$, where $n \geq 3$.

- For each k, $1 \leq k \leq n$, there is one voter $\succ_k$ of the form:
  $c_{n+1}\ c_k\ c_{k-1}\ \ldots\ c_1\ c_{k+1}\ c_{k+2}\ \ldots\ c_n$.

Let us consider the preference profile $\mathscr{P} = (\succ_1, \succ_2, \ldots, \succ_n)$. All votes have the same peak but different candidates in the second place. If this preference profile was single-peaked then these second-place candidates had to be either left or right of the peak. This is not possible for three or more candidates. Hence the profile $\mathscr{P}$ containing three or more votes is not single-peaked. By the previous argument $AA(\mathscr{P}) \geq \frac{n}{3}$. Deleting c_{n+1} however makes $\mathscr{P}$ single-peaked with respect to the axis $c_1 < c_2 < \ldots < c_n$ and hence $CD(\mathscr{P}) = LCD(\mathscr{P}) = CP(\mathscr{P}) = 1$.

Counterexample 6 (AA cannot be bounded by LS): We consider n votes over $4n$ candidates $C = \{c_1, \ldots, c_{4n}\}$.

- For each k, $1 \leq k \leq n$, there is one voter $\succ_k$ of the form:
  $c_1\ \ldots\ c_{4k-4}\ c_{4k}\ c_{4k-2}\ c_{4k-1}\ c_{4k-3}\ c_{4k+1}\ \ldots\ c_{4n}$.

Let $\mathscr{P} = (\succ_1, \ldots, \succ_n)$. The preference profile $\mathscr{P}$ is not single-peaked consistent since $\mathscr{P}[\{c_{k-3}, c_{k-2}, c_{k-1}, c_k\}]$ is neither for any $k \in \{1, \ldots, n\}$. With 5 swaps in each vote we can make these votes identical and hence $LS(\mathscr{P}) \leq 5$. Even any pair of votes in $\mathscr{P}$ is not single-peaked. Hence $AA(\mathscr{P}) \geq \frac{n}{2}$.

Counterexample 7 (CP cannot be bounded by LCD): Consider an election with $3n$ votes over the candidates $C = \{c_1, \ldots, c_{3n}\}$.

- For each k, $1 \leq k \leq 3n$, there is one voter $\succ_k$ of the form: $c_1\ \ldots\ c_{k-1}\ c_{k+1}\ \ldots\ c_{3n}\ c_k$.

Since lowest ranked candidates have to be either at the left-most or right-most position on the axis and there are more than two lowest ranked candidates, this profile is not single-peaked consistent. However, when the last ranked-candidate is removed in each vote, the profile becomes single-peaked consistent and hence $LCD(\mathscr{P}) = 1$. Concerning $CP(\mathscr{P})$ notice that any partition into n sets contains a set with at least three candidates – say c_i, c_j and c_k. But then the votes $\succ_i$, $\succ_j$ and $\succ_k$ cannot be single-peaked consistent because they rank three different candidates at the last position. Hence n candidate partitions are not enough to obtain single-peaked consistency and hence $CP(\mathscr{P}) > n$.

Counterexample 8 (CP cannot be bounded by M and AA): Consider the candidates $C = \{c_1, \ldots, c_{n^2}\}$ and the following three votes :

- There is one voter $\succ_1$ of the form: $c_1\ c_2\ \ldots\ c_{n^2}$.
- There is one voter $\succ_2$ of the form: $c_{n^2}\ c_{n^2-1}\ \ldots\ c_1$.

- There is one voter $\succ_3$ of the form:
  $c_1 \;\; c_{n+1} \;\; c_{2n+1} \;\; \cdots \;\; c_{n(n-1)+1} \;\; c_2 \;\; c_{n+2} \;\; c_{2n+2} \;\; \cdots \;\; c_{n(n-1)+2} \;\; \cdots \;\; \cdots \;\; c_n \;\; c_{2n} \;\; c_{3n} \;\; \cdots \;\; c_{n^2}.$

This preference profile is not single-peaked but $\mathrm{M}(\mathscr{P}) = 1$ and $\mathrm{AA}(\mathscr{P}) = 1$. The candidates, however, have to be partitioned into many sets in order to obtain single-peakedness. First, observe that by Lemma 4.1 we only have to consider the axis $c_1 > c_2 > \ldots > c_{n^2}$. Let us now consider vote $\succ_3$. Since we have fixed an axis we can consider longest increasing and decreasing subsequences in this vote. Note that both increasing and decreasing subsequences have a length of less than $2n$. Hence a subset of the candidates cannot be single-peaked if it contains more than $4n$ candidates. We therefore have to partition the candidates of $\mathscr{P}$ into sets of cardinality at most $4n$ and by that $\mathrm{CP}(\mathscr{P}) \geq \frac{n}{4}$. ❑

4.3 Complexity of Nearly Single-Peaked Consistency

We start with the complexity analysis of maverick single-peaked consistency. In the reduction we are going to cascade two or more preference profiles. The following definition captures this notion.

Definition 4.5. *Let $(C_1, V, \mathscr{P}_1)$ and $(C_2, V, \mathscr{P}_2)$ be two elections with $C_1 \cap C_2 = \emptyset$. Furthermore, let $\mathscr{P}_1 = (\succ'_1, \ldots, \succ'_n)$ and $\mathscr{P}_2 = (\succ''_1, \ldots, \succ''_n)$. We define $\mathscr{P}_1 \mathbin{\textcircled{$\succ$}} \mathscr{P}_2 = (\succ_1, \ldots, \succ_n)$, where for any $1 \leq i \leq n$ the linear order $\succ_i$ is defined by*

$$c \succ_i c' \text{ iff } (c, c' \in C_1 \text{ and } c \succ'_i c') \text{ or } (c, c' \in C_2 \text{ and } c \succ''_i c') \text{ or } (c \in C_1 \text{ and } c' \in C_2).$$

Note that $\mathscr{P}_1 \mathbin{\textcircled{$\succ$}} \mathscr{P}_2$ is always a preference profile over $C_1 \cup C_2$.

Lemma 4.6. *Let $(C_1, V, \mathscr{P}_1)$ and $(C_2, V, \mathscr{P}_2)$ be two elections with $C_1 \cap C_2 = \emptyset$. Assume that*

- *$\mathscr{P}_1$ and $\mathscr{P}_2$ are single-peaked consistent with respect to the axes A_1 and A_2, respectively.*
- *The preference relations in $\mathscr{P}_2$ have at most 2 peaks.*
- *These (two) peaks are adjacent on the axis A_2.*

Then $\mathscr{P}_1 \mathbin{\textcircled{$\succ$}} \mathscr{P}_2$ is single-peaked.

Proof. We are going to construct an axis A in a way that $\mathscr{P}_1 \mathbin{\textcircled{$\succ$}} \mathscr{P}_2$ is single-peaked with respect to A. First we split A_2 in two parts A'_2 and A''_2. If $\mathscr{P}_2$ contains two peaks (which have to be adjacent), we split A_2 in between these two peaks. If $\mathscr{P}_2$ contains only one peaks, we split A_2 left of the peak (this is arbitrary). The new axis A is A'_2 followed by A_1 and then A''_2, i.e., $A'_2 > A_1 > A''_2$. The correctness proof of this construction is straight-forward. ❑

Before we start with the hardness proof, let us first make the following observation.

Observation 4.7. *We are given a set of candidates $C = \{a, b, c, d\}$ and three preference relations $\succ_v$, $\succ_e$ and $\succ_{ne}$, where the candidates are ranked as follows:*

- *$a \succ_v c \succ_v b \succ_v d$,*

- *$c \succ_e b \succ_e d \succ_e a$ and*
- *$d \succ_{ne} c \succ_{ne} b \succ_{ne} a$.*

Then the preference profile $(\succ_v, \succ_e)$ is single-peaked with respect to the axis $a > c > b > d$ and $(\succ_e, \succ_{ne})$ is single-peaked with respect to the axis $d > c > b > a$. The profile $(\succ_v, \succ_{ne})$ is not single-peaked consistent.

We now show NP-hardness via a reduction from the clique problem, one of the standard NP-complete problems (see, e.g., [GJ79]). This result has been independently proven by Bredereck [Bre12].

CLIQUE

Given:	A graph (V_G, E_G) and a positive integer s.
Question:	Has the (V_G, E_G) an induced subgraph of size s that is complete, i.e. does (V_G, E_G) contain a clique of size s?

Theorem 4.8. MAVERICK SINGLE-PEAKED CONSISTENCY *is* NP-*complete.*

Proof. To show hardness we reduce from CLIQUE. Let $G = (V_G, E_G)$ be the graph in which we look for a clique of size s. Furthermore, let $V_G = \{v_1, \dots, v_n\}$ be the set of vertices and E_G the set of edges. Each vertex v_i has four corresponding candidates $c_i^1, \dots, c_i^4$. We consequently have $C = \{c_1^1, \dots, c_1^4, c_2^1, \dots, c_2^4, \dots, c_n^1, \dots, c_n^4\}$. The voters directly correspond to vertices. Therefore we define, by slight abuse of notation, $V = \{v_1, \dots, v_n\}$.

In order to define the preference relations we introduce three functions creating partial votes. In the following definition let $a, b, c, d \in C$.

$$\begin{aligned} f_v(a,b,c,d) &= a \succ c \succ b \succ d \\ f_e(a,b,c,d) &= c \succ b \succ d \succ a \\ f_{ne}(a,b,c,d) &= d \succ c \succ b \succ a \end{aligned}$$

If we consider f_v, f_e and f_{ne} as preference relations then observe that by Observation 4.7 (f_v, f_e) and (f_e, f_{ne}) are single-peaked consistent but (f_v, f_{ne}) is not.

Next we define a mapping $p(i, j)$ to a total order over the candidates $\{c_j^1, \dots, c_j^4\}$.

$$p(i,j) = \begin{cases} f_v(c_j^1, c_j^2, c_j^3, c_j^4) & \text{if } i = j \\ f_e(c_j^1, c_j^2, c_j^3, c_j^4) & \text{if } \{i,j\} \in E_G \\ f_{ne}(c_j^1, c_j^2, c_j^3, c_j^4) & \text{if } \{i,j\} \notin E_G \end{cases}$$

The intuition behind function $p(i, j)$ is to encode a row of the adjacency matrix of G as a vote in the preference profile $\mathscr{P}$. To this end, we put in "cell" (i, j) the result of f_e if there is an edge between i and j. In case there is no edge between i and j we put the result of f_{ne} in cell (i, j). In the special case $i = j$ (we are in the diagonal of the matrix) we put the result of f_v in the cell.

Let the partial profiles representing the columns of the adjacency matrix be defined as $\mathscr{P}_j = (p(1, j), \dots, p(n, j))$, for $1 \leq j \leq n$. We are now going to define the preference profile $\mathscr{P} = (\succ_1, \dots, \succ_n)$ by

$$\mathscr{P} = \mathscr{P}_1 \mathbin{\bigcirc\hspace{-0.8em}\succ} \mathscr{P}_2 \mathbin{\bigcirc\hspace{-0.8em}\succ} \dots \mathbin{\bigcirc\hspace{-0.8em}\succ} \mathscr{P}_n.$$

To conclude the construction let $E = (C, V, \mathscr{P})$ and $k = n - s$, i.e., we are allowed to delete k mavericks from E in order to obtain a single-peaked profile. The intention behind the construction is that the voters in a single-peaked profile will correspond to a clique. We claim that G has a clique of cardinality s if and only if it is possible to remove k voters from $\mathscr{P}$ in order to make the resulting preference profile single-peaked consistent.

"$\Rightarrow$" Assume that there is a clique $I = \{v_{i_1}, \ldots, v_{i_s}\}$ with $|I| = s$. Let $\mathscr{P}' = (\succ_{i_1}, \ldots, \succ_{i_s})$. By that we keep only those voters whose corresponding vertices are contained in the clique I. Observe that the election $E' = (C, I, \mathscr{P}')$ can be obtained by deleting $k = n - s$ mavericks from the election E, $|V \setminus I| = k$. It remains to show that E' is indeed single-peaked consistent. Remember that we denoted the preference relations in the j-th "column" of the profile by $\mathscr{P}_j$. By $\mathscr{P}'_j$ we denote the j-th "column" of a profile considering only the voters from $\mathscr{P}'$. Since I is a clique, for each $x, y \in I$, $x \neq y$, there is an edge $\{x, y\} \in E_G$. Thus the profile cannot contain an instantiation of f_v and of f_{ne} in the same column. By Observation 4.7, all profiles $\mathscr{P}_j$ with $1 \leq j \leq n$ are single-peaked consistent. In order to be able to apply Lemma 4.6, all conditions have to be checked. First, notice that the profiles $\mathscr{P}'_j$ and $\mathscr{P}'_{j'}$, for $1 \leq j < j' \leq n$, do not share any candidates and are single-peaked consistent. Furthermore, each of the profiles has at most two peaks. Each column contains either instantiations of f_v and f_e or instantiations of f_e and f_{ne}. Otherwise it would not be single-peaked consistent. But then there are only two top-ranked candidates, i.e., either the candidates top-ranked by f_v and f_e, or the candidates top-ranked by f_e and f_{ne}. Finally, the two top-ranked candidates of $\mathscr{P}'_j$ have to be adjacent on the axis which gives single-peaked consistency. Consider again Observation 4.7. For (f_v, f_e) the top-ranked candidates a and c are adjacent on the axis $a > c > b > d$. The same holds for (f_e, f_{ne}) with axis $d > c > b > a$ and c, d as top-ranked candidates. Since all conditions are fulfilled, we can iteratively apply Lemma 4.6. Therefore, $\mathscr{P}'_1 \ogreaterthan \mathscr{P}'_2, (\mathscr{P}'_1 \ogreaterthan \mathscr{P}'_2) \ogreaterthan \mathscr{P}'_3, \ldots, (\mathscr{P}'_1 \ogreaterthan \ldots) \ogreaterthan \mathscr{P}'_n$ and hence also $\mathscr{P}'$ are single-peaked consistent.

"$\Leftarrow$" Assume that $E' = (C, V', \mathscr{P}')$ is an election that has been obtained from E by deleting k voters such that $\mathscr{P}'$ is single-peaked. Consequently $|V'| = s$. Let $V' = \{v_{i_1}, \ldots, v_{i_s}\}$ and $\mathscr{P}' = (\succ_{i_1}, \ldots, \succ_{i_s})$.

We claim that V' is a clique in G. By Lemma 4.3 we know that each of the n columns $(\mathscr{P}'_1, \ldots, \mathscr{P}'_n)$ of $\mathscr{P}'$ is single-peaked consistent. Then, by Observation 4.7, each column must not contain an instance of f_v together with an instance of f_{ne}. (Otherwise the respective column would not be single-peaked consistent!) Observe that by construction each vote (in $\mathscr{P}'$) contains an instance of f_v in some column. But then each vertex must be adjacent to all other vertices – in other words V' is a clique. ❑

We now turn to additional axes single-peaked consistency. Here we make use of a similar construction as presented in Theorem 4.8 with the difference that we now show NP-hardness via a reduction from the partition into cliques problem, which is also one of the standard NP-complete problems (see, e.g., [GJ79]).

PARTITION INTO CLIQUES

Given:	A graph (V_G, E_G) and a positive integer s.
Question:	Is it possible to partition V_G into s sets such that each set of vertices induces a clique on (V_G, E_G)?

Theorem 4.9. ADDITIONAL AXES SINGLE-PEAKED CONSISTENCY *is* NP-*complete.*

Proof. Hardness is shown by a reduction from PARTITION INTO CLIQUES. For the reduction we use the same transformation as presented in the proof of Theorem 4.8 to obtain an election. Then we set $k = s-1$, i.e., we are searching for a partition of the voters into s disjoint sets such that each of the partitions is single-peaked consistent. Due to the one-to-one correspondence between voters and vertices we can use the partition of the vertices to obtain a partition of the voters and vice versa. With arguments similar to the proof of Theorem 4.8 one can show that a set of vertices is a clique if and only if the corresponding profile is single-peaked consistent. ❑

Remark 4.10. *The* PARTITION INTO CLIQUES *problem is* NP-*complete even when one is asked to partition the graph into three cliques. Consequently it follows from the proof of Theorem 4.9 that* ADDITIONAL AXES SINGLE-PEAKED CONSISTENCY *is* NP-*complete even for* $k = 2$*, i.e., for checking single-peaked consistency with two additional axes.*

In the proofs of our next two results, we will provide reductions from the NP-complete problem MINIMUM RADIUS, which was shown to be NP-complete in [FL97] and is defined as follows:

MINIMUM RADIUS

Given:	A set of strings $S \subseteq \{0,1\}^n$ and a positive integer s.
Question:	Has S a radius of at most s, i.e., is there a string $\alpha \in \{0,1\}^n$ such that each string in S has a Hamming distance of at most s to α?

Theorem 4.11. LOCAL CANDIDATE DELETION SINGLE-PEAKED CONSISTENCY *is* NP-*complete.*

Proof. A MINIMUM RADIUS instance is given by $S \subseteq \{0,1\}^m$, the set of binary strings, and a positive integer s. Given a string β, let $\beta(k)$ denote the bit value at the k-th position in β. We are going to construct an LCD SINGLE-PEAKED CONSISTENCY instance. Each string in $S = \{\beta_1,\dots,\beta_n\}$ will correspond to a voter. Each bit of the strings corresponds to two candidates. In addition, we have $2ms+2$ extra candidates. Consequently, we have $C = \{c_1^1, c_1^2, c_2^1, c_2^2, \dots, c_n^1, c_n^2, c'_1, \dots, c'_{ms+1}, c''_1, \dots, c''_{ms+1}\}$.

We define the preference profile with the help of two functions creating total orders.

$$f_0(a,b) = a \succ b \qquad\qquad f_1(a,b) = b \succ a$$

The vote $\succ_k$, for each $k \in \{1,\dots,m\}$, is of the form

$$c'_1 \ \dots\ c'_{ms+1}\ \ f_{\beta_k(1)}(c_1^1,c_1^2)\ \ f_{\beta_k(2)}(c_2^1,c_2^2)\ \ \dots\ \ f_{\beta_k(n)}(c_n^1,c_n^2)\ \ c''_1\ \dots\ c''_{ms+1}.$$

The preference profile $\mathscr{P}$ is now defined as $(\succ_1,\dots,\succ_n,\overline{\succ_1},\dots,\overline{\succ_n})$. We claim that $(C,V,\mathscr{P})$ is s-LCD single-peaked consistent if and only if S has a radius of at most s.

"$\Leftarrow$" Suppose that S has a radius of at most s, i.e., there is a string $\alpha \in \{0,1\}^n$ with Hamming distance at most s to each $\beta \in S$. We consider the following axis A:

$$c'_1 > \dots > c'_{ms+1} > f_{\alpha(1)}(c_1^1,c_1^2) > f_{\alpha(2)}(c_2^1,c_2^2) > \dots f_{\alpha(n)}(c_n^1,c_n^2) > c''_1 > \dots > c''_{ms+1}.$$

We claim that $\mathscr{P}$ is single-peaked with respect to A after deleting at most s candidates in each vote. The deletions for vote $\succ_k$, $k \in \{1,\dots,m\}$, are the following: We delete candidate c_i^1 in $\succ_k$ if and only if $\alpha(i) \neq \beta_k(i)$. The deletions in $\overline{\succ_k}$ are exactly the same as in $\succ_k$. These are at most s deletions since the Hamming distance between α and every $\beta \in S$ is at most s. After these deletions all votes are either subsequences of A or its reverse. Hence we obtain a single-peaked consistent profile.

"$\Rightarrow$" Let $\mathscr{P}'$ be the partial, single-peaked consistent profile that was obtained by deleting at most s candidates in each vote. First, note that some $c' \in \{c'_1, \dots, c'_{ms+1}\}$ has not been deleted in any vote since in total at most $m \cdot s$ many different candidates can be deleted. In the same way let $c'' \in \{c''_1, \dots, c''_{ms+1}\}$ be a candidate that has not been deleted in any vote. Now let us consider the profile $\mathscr{P}'[\{c', c'', c_i^1, c_i^2\}]$ for any $i \in \{1, \dots, n\}$. We claim that α, defined in the following way, has a Hamming distance of at most s to all bitstrings in S.

$$\alpha(k) = \begin{cases} 0 & \text{if } \mathscr{P}' \text{ contains the vote } c' \succ c_i^1 \succ c_i^2 \succ c'', \\ 1 & \text{if } \mathscr{P}' \text{ contains the vote } c' \succ c_i^2 \succ c_i^1 \succ c'', \\ 1 & \text{otherwise.} \end{cases}$$

First, observe that Case 1 and 2 cannot occur at the same time since then $\mathscr{P}'$ would not be single-peaked consistent. This is because $\mathscr{P}'[\{c', c'', c_i^1, c_i^2\}]$ also contains votes where c'' is ranked top and c' is ranked last and hence either $c' \succ c_i^1 \succ c_i^2 \succ c''$ or $c' \succ c_i^2 \succ c_i^1 \succ c''$ would not be single-peaked.

Let $\beta_j \in S$, $j \in \{1, \dots, n\}$. Note that if at any position i, $\beta_j(i) \neq \alpha(i)$ then either c_i^1 or c_i^2 had to be deleted in the vote $\succ_j$. Otherwise $\mathscr{P}'$ would not be single-peaked consistent. Hence the set $\{k \in \{1, \dots, m\} \mid \alpha(i) \neq \beta_j(i)\}$ cannot contain more than s elements because this would require more than s candidate deletions in the corresponding vote $\succ_j$. Hereby we have shown that the Hamming distance of α and β_j is at most s. ❑

Theorem 4.12. LOCAL SWAPS SINGLE-PEAKED CONSISTENCY *is* NP-*complete.*

Proof. We use the same construction as in the proof of Theorem 4.11. It holds that $(C, V, \mathscr{P})$ is s-LS single-peaked consistent if and only if S has a radius of at most s. This can be shown similarly to the proof of Theorem 4.11 except that we swap elements instead of deleting them. ❑

The following problem will be useful for showing NP-hardness of GLOBAL SWAPS SINGLE-PEAKED CONSISTENCY. Given two votes, $\succ_x$ and $\succ_y$, let $\mathsf{swaps}(\succ_x, \succ_y)$ denote the minimum number of swaps of adjacent candidates needed to make $\succ_x$ and $\succ_y$ equal.

KEMENY OPTIMAL AGGREGATION

Given:	An election $(C, V, \mathscr{P})$, with $\mathscr{P} = (\succ_1, \dots, \succ_n)$, and an integer s.
Question:	Is there a vote $\succ^*$ over C such that $\sum_{1 \leq i \leq n} \mathsf{swaps}(\succ_i, \succ^*) \leq s$.

KEMENY OPTIMAL AGGREGATION was shown to be NP-hard in [BTT89b]. This result was strengthened in [DKNS01] to require only four voters.

Theorem 4.13. GLOBAL SWAPS SINGLE-PEAKED CONSISTENCY *is* NP-*complete.*

Proof. We show NP-hardness of this problem by reduction from KEMENY OPTIMAL AGGREGATION. Let a KEMENY OPTIMAL AGGREGATION instance be given by $(C, V, \mathscr{P})$ and an integer s. Furthermore, let $C = \{c_1, \dots, c_m\}$, $\mathscr{P} = (\succ_1, \dots, \succ_n)$ and let k be defined as $2s$.

We create a new election $(C',V,\mathscr{P}')$ with $C' = C \cup \{c_1^{\text{top}},\dots,c_{2k+1}^{\text{top}},c_1^{\text{last}},\dots,c_{2k+1}^{\text{last}}\}$, i.e. $|C'| = m+4k+2$.

For each $i \in \{1,\dots,m\}$ we create two votes $\succ_i'$ and $\succ_i''$ as follows. The vote $\succ_i'$ ranks c_1^{top} first, followed by c_2^{top}, c_3^{top}, …, c_{2k}^{top} and finally c_{2k+1}^{top}. Then it ranks the candidates in C in the same order as $\succ_i$ does. Finally, it orders the candidates $c_1^{\text{last}} \cdots c_{2k+1}^{\text{last}}$ with descending preference, i.e. c_{2k+1}^{last} being the last ranked candidate. The preference profile $\mathscr{P}'$ is now defined as $(\succ_1', \overline{\succ_1'}, \dots, \succ_n', \overline{\succ_n'})$.

We claim that $(C',V,\mathscr{P}')$ is k-GS single-peaked consistent if and only if $(V,C,\mathscr{P})$ and s are a yes-instance of the KEMENY OPTIMAL AGGREGATION problem.

"⇒" Suppose that $(C',V,\mathscr{P}')$ is k-GS single-peaked consistent. Therefore, one can obtain the profile $\mathscr{P}^S$ from $\mathscr{P}'$ by applying at most $k = 2s$ swaps such that $\mathscr{P}^S$ is single-peaked consistent with respect to an axis A. Since there are $2k+1$ candidates in the set $\{c_1^{\text{top}},\dots,c_{2k+1}^{\text{top}}\}$ at least one of them must have remained in place in each vote. Analogously, the same holds for one of the candidates contained in the set $\{c_1^{\text{last}},\dots,c_{2k+1}^{\text{last}}\}$. Let c_{top} (resp. c_{last}) denote these two candidates. From Lemma 4.3 we know that $\mathscr{P}^S[\{c_{\text{top}},c_1,\dots,c_m,c_{\text{last}}\}]$ is single-peaked consistent as well. Observe that all primed votes in $\mathscr{P}^S[\{c_{\text{top}},c_1,\dots,c_m,c_{\text{last}}\}]$ have c_{top} as peak and c_{last} as last candidate, while in the double-primed votes c_{last} is top and c_{top} is the last ranked candidate. By Lemma 4.1 all primed votes in $\mathscr{P}^S[\{c_1,\dots,c_m\}]$ must be ordered in the same way. We denote this ordering by $\succ^*$. The double-primed votes in $\mathscr{P}^S[\{c_1,\dots,c_m\}]$, however, must be ordered according to the reverse of $\succ^*$. Notice that turning the primed votes into $\succ^*$ requires the same number of swaps as turning the double-primed votes into the reverse of $\succ^*$. Therefore, $\frac{k}{2} = s$ swaps are sufficient to turn all primed votes into $\succ^*$. Taken together, $\succ^*$ fulfills all properties to be a yes-instance of the KEMENY OPTIMAL AGGREGATION problem.

"⇐" Assume $(C,V,\mathscr{P})$ and s describe a yes-instance of the KEMENY OPTIMAL AGGREGATION problem. Then there is some common ordering $\succ^*$, which has in total a swap distance of $\leq s$ to all votes in $\mathscr{P}$. Let A^* be an axis ordering the candidates in C in the same way as $\succ^*$ does. Then, $(C',V,\mathscr{P}')$ is k-GS single-peaked consistent with respect to the axis $c_1^{\text{top}} > c_2^{\text{top}} > \cdots > c_{2k+1}^{\text{top}} > A^* > c_1^{\text{last}} > c_2^{\text{last}} > \cdots > c_{2k+1}^{\text{last}}$. This is because all votes can be brought into the form $c_1^{\text{top}} \succ c_2^{\text{top}} \succ \cdots \succ c_{2k+1}^{\text{top}} \succ [c_1,\dots,c_n \text{ as ordered by } \succ^*] \succ c_1^{\text{last}} \succ c_2^{\text{last}} \succ \cdots \succ c_{2k+1}^{\text{last}}$ or its reverse by using at most $k = 2s$ swaps – s swaps for the primed votes and s swaps for the double-primed votes. ❑

Remark 4.14. *Since* KEMENY OPTIMAL AGGREGATION *with only four voters is* NP-*complete [DKNS01], it follows from the proof of Theorem 4.13 that* GLOBAL SWAPS SINGLE-PEAKED CONSISTENCY *is* NP-*complete even for eight voters.*

In contrast to the previous hardness results, we are able to show that CANDIDATE DELETION SINGLE-PEAKED CONSISTENCY can be decided in polynomial time. The algorithm builds upon the $\mathscr{O}(|V| \cdot |C|)$. time algorithm for testing single-peaked consistency by Escoffier, Lang and Ötztürk [ELÖ08]. Since we make some modifications to the algorithm and also for the sake of completeness we present it here as well.

For the remainder of this section let $(C,V,\mathscr{P})$ be an election with $|V| = n$ and $C = \{c_1,\dots,c_m\}$.

The single-peaked consistency algorithm. This algorithm is a slightly adapted version of the algorithm by Escoffier, Lang and Ötztürk [ELÖ08]. We start by giving three fundamental definitions that we use to state the algorithm.

Definition 4.15. *$L(\mathscr{P},C')$ is the set of last ranked candidates in $\mathscr{P}[C']$.*

Definition 4.16. *A* partial axis *A is a total order of a subset of the candidates in C. Let $cand(A)$ denote the candidates that are ordered by A. Consequently, any partial axis A is an axis over $cand(A)$. By the* cardinality of a partial axis *A we mean $|cand(A)|$.*

Definition 4.17. *An* incomplete axis *is a partial axis with a marked position that indicates where further elements may be added. We denote this position by three dots, e.g., the incomplete axis $c_1 > c_2 > \cdots > c_3$ allows additional candidates to be added right of c_2 and left of c_3. The* boundary *of an incomplete axis A, $boundary(A)$, are the two elements left and right of the dots, e.g., $boundary(c_1 > c_2 > \cdots > c_3) = \{c_2,c_3\}$.*

In order to allow for a more concise description of the algorithm, we assume that there are two additional candidates c_0 and c_0'. The candidate c_0 is ranked last in every vote and c_0' is ranked second-to-last, i.e., $L(\mathscr{P},C) = \{c_0\}$ and $L(\mathscr{P},C \setminus \{c_0\}) = \{c_0'\}$. All other candidates are ranked above these. Note that these modified votes are single-peaked consistent if and only if the original votes were single-peaked consistent. Indeed, any axis for the original votes is an axis for the modified votes if we add c_0 at the leftmost position and c_0' at the rightmost position (or vice versa). Conversely, every axis of the modified votes is an axis of the original votes if c_0 and c_0' are removed. Due to these observations we can assume that the algorithm always starts with the incomplete axis $c_0 > \ldots > c_0'$.

The algorithm now proceeds iteratively by placing the least ranked candidates that have not yet been placed. Let C' be the set of candidates that have not yet been positioned on the (incomplete) axis A. The algorithm checks what kinds of constraints follow from each vote. If these constraints do not contradict each other, the set of least ranked candidates $L(\mathscr{P},C')$ is placed. We denote this procedure with $\mathsf{place}(A,X)$ where $X = L(\mathscr{P},C')$. The procedure $\mathsf{place}(A,X)$ returns either a new incomplete axis (extending A by the candidates in X) or the value `INCONSISTENT`. The single-peaked consistency algorithm repeatedly invokes place until all elements have been placed or a contradiction has been found.

Now we would like to describe $\mathsf{place}(A,X)$ in detail since it is used also by the candidate deletion algorithm. Let $boundary(A) = \{b_1,b_2\}$. The following cases are considered for each vote $\prec_k$, $k \in \{1,\ldots,n\}$ and thus we obtain constraints on possible placements of X.

Case 1: $|L(\mathscr{P},C')| \geq 3$. There are three or more candidates that would have to be placed at the positions next to b_1 and b_2. Since this is not possible, $\mathscr{P}$ is not single-peaked consistent.

Case 2: $L(\mathscr{P},C') = \{x_1,x_2\}$. The candidates x_1 and x_2 have to be placed at the positions next to b_1 and next to b_2.

(a) $x_1 \prec_k b_1$ and $x_1 \prec_k b_2$: This is not possible because then x_1 would already have been placed in a previous iteration step.

(b) $b_1 \prec_k x_1$ and $b_2 \prec_k x_1$: There are no constraints for x_1 that follow from vote $\succ_k$.

(c) $b_1 \prec_k x_1 \prec_k b_2 \prec_k x_2$: x_1 has to be placed next to b_1 and therefore x_2 is placed next to b_2.

(d) $b_1 \prec_k x_1 \prec_k x_2 \prec_k b_2$: x_1 has to be placed next to b_1 and therefore x_2 has to be placed next to b_2.

All these rules are also applicable if b_1 and b_2 are interchanged and also if x_1 and x_2 are interchanged.

Case 3: $L(\mathscr{P},C') = \{x\}$. The candidate x has to be placed either at the position next b_1 or b_2.

(a) $x \prec_k b_1$ and $x \prec_k b_2$: This is not possible because then x_1 would already have been placed in a previous iteration step.

(b) $b_1 \prec_k x$ and $b_2 \prec_k x$: There are no constraints for x.

(c) $b_1 \prec_k x \prec_k b_2$: x has to be placed next to b_1.

(d) $b_2 \prec_k x \prec_k b_1$: x has to be placed next to b_2.

This case distinction yields constraints on placing X for each vote $\prec_k$. If there is a way to place the candidates in X that is compatible with every vote, $\mathsf{place}(A,X)$ has been successful and returns the new incomplete axis. Otherwise the value `INCONSISTENT` is returned.

Observation 4.18. *The placement of candidates in the* place *procedure does only depend on* $boundary(A)$ *rather than the full partial axis* A.

The candidate deletion algorithm. The basic data structure consists of an incomplete axis A (as in the single-peaked consistency algorithm) and a set of candidates X that have been placed on A in the previous iteration of the algorithm. We refer to this data structure as *state*. The algorithm will maintain a set $\mathscr{S}$ of possible states. By removing unnecessary states the cardinality of $\mathscr{S}$ will be in $\mathscr{O}(|C|^2)$.

The algorithm utilizes dynamic programming. Given a state (A,X) and a set of candidates X_{new} that are to be placed next, we try to obtain a new incomplete axis A_{new}. If such an incomplete axis A_{new} can be found, it extends A by the candidates in X_{new}. The placement is performed by the place procedure, more precisely we call $\mathsf{place}(A,X_{new})$. Since placing more than two candidates at once is not possible, we always have $|X_{new}| \leq 2$. As in the single-peaked consistency algorithm we start with the incomplete axis $A_0 = c_0 \succ \ldots \succ c_0'$. The starting state is consequently $(A_0,\{c_0'\})$.

For a concise description of the algorithm see Algorithm 1. Similar to the single-peaked consistency algorithm we place lower ranked candidates first. However, in contrast to the previously described single-peaked consistency algorithm we may delete candidates. Hence there are several possibilities which candidates are to be placed next. We define a set $next(X)$ containing those candidates that may be placed next. For this let $X = \{x_1,x_2\}$, with $x_1 = x_2$ in case $|X| = 1$. We define

$$next(X) = \{c \in C \mid \forall k \in \{1,\ldots,|V|\}\ (c \succ_k x_1) \vee (c \succ_k x_2)\}\,.$$

Candidates that are not contained in $next(X)$ have already been processed, i.e., they have already been placed on the axis or have been deleted. Consequently, the set of candidates that have been deleted so far is exactly $C \setminus (cand(A) \cup next(X))$.

Recall that placing three or more candidates by the place procedure at once is not possible. Therefore, we consider every set of candidates $X_{new} \subseteq next(X)$ of cardinality 1 or 2. If $|X_{new}| = 2$ an additional condition has to apply. There has to be a vote $\succ$ for which $x_1 \succ x_2$ holds and another vote for which $x_2 \succ x_1$ holds. This condition is equivalent to requiring that $L(\mathscr{P},X_{new}) = X_{new}$. (If this condition is not satisfied, the lower ranked candidate has to be placed first and the higher ranked

Algorithm 1: Polynomial time algorithm for k-CD single-peaked consistency – Theorem 4.19

```
$(A_{\text{init}}, X_{\text{init}}) = \big(c_0 > \cdots > c'_0, \{c'_0\}\big)$
$\mathscr{S} \leftarrow \big\{(A_{\text{init}}, X_{\text{init}})\big\}$      // The set $\mathscr{S}$ contains all states under consideration
repeat $m$ times
    $\mathscr{S}_{\text{new}} \leftarrow \emptyset$
    foreach state $(A, X) \in \mathscr{S}$ do
        foreach $X_{new} \subseteq next(X)$ with $1 \leq |X_{new}| \leq 2$ and $L(\mathscr{P}, X_{new}) = X_{new}$ do
            $A_{new} \leftarrow \mathsf{place}(A, X_{\text{new}})$
            if $A_{new} \neq$ INCONSISTENT then
                Add the state $(A_{\text{new}}, X_{\text{new}})$ to $\mathscr{S}_{\text{new}}$
    $\mathscr{S} \leftarrow \mathscr{S} \cup \mathscr{S}_{\text{new}}$
    foreach pair of states $\{(A, X), (A', X')\} \subseteq \mathscr{S}$ do
        if $boundary(A) = boundary(A')$ and $X = X'$ then
            if $|cand(A)| \leq |cand(A')|$ then remove $(A, X)$ from $\mathscr{S}$
            else remove $(A', X')$ from $\mathscr{S}$
return the state $(A, X) \in \mathscr{S}$ with the maximum $|cand(A)|$
```

candidate in a later iteration step. Note that also in the single-peaked consistency algorithm lower ranked candidates are always placed first.)

If $\mathsf{place}(A, X_{new})$ returns a new incomplete axis A_{new}, we have obtained a new state (A_{new}, X_{new}). This state is added to the set of new states $\mathscr{S}_{new}$. If placing the candidates in X_{new} on A is not possible (i.e., $\mathsf{place}(A, X_{new}) = \texttt{INCONSISTENT}$), no state is added to $\mathscr{S}_{new}$.

The algorithm applies $\mathsf{place}(A, X_{new})$ for every incomplete axis A of every state $(A, X) \in \mathscr{S}$ and for every admissible $X_{new} \subseteq next(X)$. After this, we have obtained a set $\mathscr{S}_{new}$ containing the new states. Now the elements of $\mathscr{S}_{new}$ are added to $\mathscr{S}$. Some of these states may be comparable in the following sense. If two states have the same X set, they have the same set of candidates that are not yet placed and not yet deleted. If two states have the same boundary, they are indistinguishable from the perspective of the place procedure (cf. Observation 4.18). Therefore if two states have both the same boundary and the same X set, we can discard the state where more candidates had to be deleted so far. This is the same as discarding the state with the smaller incomplete axis. In case that two such states have incomplete axes of the same cardinality, we make the choice arbitrarily.

So far, we have seen the application of the place procedure followed by the discarding step. These two steps are repeated m times by the algorithm. Any sequence of states leading to a cardinality maximal partial axis has cardinality at most m because in each step at least one candidate is placed on the axis. Therefore the algorithm stops at this point and the set $\mathscr{S}$ contains a partial axis of maximum cardinality.

Theorem 4.19. Candidate Deletion Single-Peaked Consistency *can be solved in time* $\mathscr{O}(|V| \cdot |C|^5)$.

Proof. The runtime bound can be seen as follows. After discarding states in $\mathscr{S}$ that are not necessary, states can be uniquely identified by their boundary and by the set X. Note that X is a non-empty subset of $\mathit{boundary}(A)$ and $\mathit{boundary}(A)$ is a cardinality 2 subset of C. Therefore there are $\binom{|C|}{2}$ different boundaries, each of which has three compatible X sets. We see that here are at most $3 \cdot |C|^2$ states in $\mathscr{S}$. For each of these states and for each pair of candidates, we employ the place procedure. This procedure has a runtime of $\mathscr{O}(|V|)$. In total this yields a runtime of $\mathscr{O}(|V| \cdot |C|^4)$ for one iteration step. Discarding unwanted states can be done in time $\mathscr{O}(|C|^4)$ by checking every pair of states. The place procedure and discarding step is repeated $|C|$ times. We obtain a total runtime of $\mathscr{O}(|V| \cdot |C|^5)$.

The correctness of the algorithm can be seen as follows. Let A be a partial axis over C with maximum cardinality such that $\mathscr{P}[\mathit{Cand}(A)]$ is single-peaked with respect to A. The candidate deletion algorithm should either find this partial axis or a partial axis of same cardinality that yields single-peaked consistency as well. If we consider the election $(\mathit{Cand}(A), V, \mathscr{P}[\mathit{Cand}(A)])$ the single-peaked consistency algorithm finds either the axis A or a permutation of A for which $\mathscr{P}[\mathit{Cand}(A)]$ is single-peaked as well. As we know from the description of the single-peaked consistency algorithm, this is achieved by placing all candidates on the axis, at most two at a time. Let $X_1, X_2, \dots, X_{m'}$, $m' \leq m$, denote this sequence of singletons or pairs of candidates. Furthermore, let $A_1, A_2, \dots, A_{m'}$ be the sequence of incomplete axes generated by iterative application of the place procedure. These two sequences yield a sequence of states that can also be generated by the candidate deletion algorithm. Let A_0 denote the starting axis $c_0 > \dots > c_0'$ (as described in the single-peaked consistency algorithm). In the first iteration the state (A_1, X_1) is generated since $A_1 = \mathsf{place}(A_0, X_1)$. Moreover, it holds in general that $A_k = \mathsf{place}(A_{k-1}, X_k)$ for every $k \in \{1, \dots, m'\}$. If we disregard that some states might be discarded by the algorithm, this shows that indeed after $m' \leq m$ iterations the state $(A_{m'}, X_{m'})$ is contained in $\mathscr{S}$. Since $|\mathit{cand}(A_{m'})| = |\mathit{cand}(A)|$ this is a partial axis of maximum cardinality.

It remains to deal with the issue that at some point a state (A_k, X_k), $k \in \{1, \dots, m'\}$, may be discarded in favor of some other state (A_k', X_k). This can only happen if $\mathit{boundary}(A_k) = \mathit{boundary}(A_k')$ and $|\mathit{cand}(A_k)| \leq |\mathit{cand}(A_k')|$. Recall that the place procedure depends only on X and $\mathit{boundary}(A)$. Therefore it holds that $\mathit{boundary}(\mathsf{place}(A_k', X_k')) = \mathit{boundary}(\mathsf{place}(A_k, X_k))$, i.e., $\mathsf{place}(A_k', X_k)$ yields an incomplete axis A_{k+1}' with $\mathit{boundary}(A_{k+1}') = \mathit{boundary}(A_{k+1})$. We see that discarding states might prevent the algorithm from finding the partial axis $A_{m'}$ but we still obtain an axis of same cardinality. (We cannot obtain an axis of larger cardinality since we assumed A to be of maximum cardinality.)

Finally, we would like to show that $\mathscr{P}$ is single-peaked with respect to all partial axes computed by the algorithm. Let A be a partial axis obtained by the candidate deletion algorithm and let $(A_1, X_1), (A_2, X_2), \dots, (A_{m'}, X_{m'})$ denote the sequence of states that led to $A = A_{m'}$, i.e., $A_k = \mathsf{place}(A_{k-1}, X_k)$ holds for every $k \in \{1, \dots, m'\}$. Observe that $L(\mathscr{P}, \mathit{cand}(A) \setminus \bigcup_{i=1}^{k-1} X_i) = X_k$ for every $k \in \{1, \dots, m'\}$. (This holds because of the condition $L(\mathscr{P}, X_{new}) = X_{new}$ in Line 6 of the algorithm.) The single-peaked consistency algorithm – applied to the election $(\mathit{cand}(A), V, \mathscr{P}[\mathit{cand}(A)])$ – would therefore yield the same axis A. Hence the election $(\mathit{cand}(A), V, \mathscr{P}[\mathit{cand}(A)])$ is single-peaked. ❑

5 Manipulation

We start with an easy observation which we will use to prove Theorem 5.2.

Corollary 5.1. *Let $X \in \{$candidate deletion, local candidate deletion, additional axes, global swaps, local swaps$\}$. If an election E over three candidates is 1-maverick single-peaked consistent, then it is also 1-X single peaked consistent and 2-candidate partition single-peaked consistent.*

Proof. It is easy to see that every election over three candidates is 1-candidate deletion, 1-local candidate deletion, and 2-candidate partition single-peaked consistent. From Theorem 4.4, (6) follows, that E is also 1-additional axes single-peaked consistent.

Let $C = \{a, b, c\}$ be the set of candidates, and without loss of generality assume that E is 1-maverick single-peaked consistent along the axis $a < b < c$. Note that there are only two possible maverick votes, *acb* and *cab*. Swaping in both votes the last two candidates leaves us with single-peaked votes with respect to axis $a < b < c$. Thus, E is 1-global swaps single-peaked consistent. From Theorem 4.4, (1) follows, that E is 1-local swaps single-peaked consistent. ❑

Following the notation of [FHH11], let $(\alpha_1, \alpha_2, \alpha_3)$ *elections* denote three-candidate scoring rule elections using the scoring-vector $\alpha = (\alpha_1, \alpha_2, \alpha_3)$. In that paper it was proved that for each $\alpha_1 \geq \alpha_2 > \alpha_3$, $(\alpha_1, \alpha_2, \alpha_3)$-1-MAVERICK-CCWM is NP-complete. This result is interesting, especially in the case of veto elections, because it means that VETO-1-MAVERICK-CCWM for three-candidate elections is NP-complete although VETO-CCWM is in P in single-peaked societies. The following theorem shows that the same holds for all the other notions presented in this paper.

Theorem 5.2. *Let $X \in \{$candidate deletion, local candidate deletion, additional axes, global swaps, local swaps$\}$. For each $\alpha_1 \geq \alpha_2 > \alpha_3$, $(\alpha_1, \alpha_2, \alpha_3)$-1-X-CCWM and $(\alpha_1, \alpha_2, \alpha_3)$-2-CANDIDATE PARTITION-CCWM are NP-complete.*

Proof. The same proof as in the technical report version of [FHH11], Theorem 3.1, holds. In their proof, Faliszewski et al. construct a three-candidate election which is 1-maverick single-peaked consistent. According to Corollary 5.1, that election is also 1-X single peaked consistent and 2-candidate partition single-peaked consistent and thus the same proof holds. ❑

In the remainder of this section we study the complexity of constructive coalitional weighted manipulation in nearly single-peaked societies under the veto rule. Table 2 summarizes the complexity results regarding VETO-X-CCWM under several notions of nearly single-peakedness. In the following we will prove each entry of this table. All reductions are from the NP-complete problem PARTITION (see, e.g., [GJ79]).

PARTITION	
Given:	A finite multiset $S = \{k_1, \dots, k_s\}$ of positive integers such that $s > 0$ and $\sum_{i=1}^{s} k_i = 2K$.
Question:	Is there a subset $S' \subset S$ such that the sum of the elements in S' is exactly K?

Theorem 5.3. *Let $m \geq 3$ denote the number of candidates. For each $\ell \geq 0$, VETO-ℓ-CANDIDATE DELETION-CCWM is in P if $\ell \leq m - 3$ and NP-complete otherwise.*

Proof. We can argue in a similar way as Faliszewski et al. did for ℓ-maverick societies [FHH11] . We are first handling the $\ell \leq m-3$ case. Let A be the axis along the election is nearly single-peaked and let c_l and c_r be the leftmost and rightmost candidates in A, respectively. Note that in a veto election over a single-peaked society, the candidates other than c_l and c_r are never vetoed. In an

X	P	NP-complete	Reference
ℓ-Maverick	$\ell \leq m-3$	$\ell > m-3$	[FHH11]
ℓ-Candidate Deletion	$\boldsymbol{\ell \leq m-3}$	$\boldsymbol{\ell > m-3}$	Thm. 5.3
ℓ-Local Candidate Deletion	$\boldsymbol{n \leq m-1}$	$\boldsymbol{n > m-1}$	Thm. 5.4
ℓ-Global Swaps	$m = 2k$: $\boldsymbol{\ell \leq k^2 - k - 1}$ $m = 2k-1$: $\boldsymbol{\ell \leq k^2 - 2k}$	$\boldsymbol{\ell > k^2 - k - 1}$ $\boldsymbol{\ell > k^2 - 2k}$	Thm. 5.6 Thm. 5.6
ℓ-Local Swaps	$\boldsymbol{\ell \leq \lfloor \frac{m-1}{2} \rfloor - 1}$	$\boldsymbol{\ell > \lfloor \frac{m-1}{2} \rfloor - 1}$	Thm. 5.7
ℓ-Candidate Partition	$\boldsymbol{\ell \leq \lfloor \frac{m-1}{2} \rfloor}$	$\boldsymbol{\ell > \lfloor \frac{m-1}{2} \rfloor}$	Thm. 5.8
ℓ-Additional Axes	$\boldsymbol{\ell \leq \lfloor \frac{m-1}{2} \rfloor - 1}$	$\boldsymbol{\ell > \lfloor \frac{m-1}{2} \rfloor - 1}$	Thm. 5.9

Table 2: Complexity results regarding VETO-X-CCWM under several notions of nearly single-peakedness. Results in boldface are new results, the other two results are due to Faliszewski et al. [FHH11].

ℓ-candidate deletion nearly single-peaked society there could be an additional ℓ candidates vetoed in those votes not consistent with the axis A. These are overall $\ell + 2$ candidates. Since $\ell \leq m-3$, there has to be at least one candidate who never got vetoed. Thus, manipulation is only possible if the distinguished candidate is amongst the candidates who never got vetoed by the nonmanipulators.

The hardness proof is similar to the proof given in [FHH11] for the maverick case. ❑

The following theorem shows that ℓ-local candidate deletion is the only nearly single-peaked notion, where the complexity of veto constructive coalitional weighted manipulation is independent of ℓ. In this case we require that $\ell \geq 1$. The $\ell = 0$ case would mean that the election is single-peaked, for which Brandt et al. [BBHH10] proved that constructive coalitional weighted manipulation is in P.

Theorem 5.4. *Let $m \geq 3$ be the number of candidates and n be the number of voters (consisting of the manipulators and the nonmanipulators). For each $\ell \geq 1$,* VETO-ℓ-LOCAL CANDIDATE DELETION-CCWM *is in* P *if $n \leq m-1$ and* NP*-complete otherwise.*

Proof. We can again argue similarly to the previous proof. Since we can delete in each vote at least one candidate, at most n different candidates can be vetoed. Since $n < m$, there has to be at least one candidate who never got vetoed. Thus, manipulation is only possible if the distinguished candidate is amongst the candidates who never got vetoed by the nonmanipulators.

The hardness proof is similar to the general case (non-single-peaked societies) proven by Conitzer et al. [CSL07]. ❑

In the following, for any two candidates $c_1, c_2 \in C$ let $d_A(c_1, c_2)$ be the *distance of two candidates on the axis A*. For example, for the axis $A = c_1c_3c_5c_4c_2c_6$ the distance $d_A(c_1, c_2) = 4$.

Lemma 5.5. *Let $E = (C, V, \mathscr{P})$ be a single-peaked election along the axis A, where c_l and c_r are the leftmost and rightmost candidates, respectively. The number of swaps required to make a candidate $c \in C$ the lowest-ranked candidate in a vote $v \in V$ is at least $min(d_A(c, c_r), d_A(c, c_l))$.*

Proof. Without loss of generality assume that c is closer to c_r in A than to c_l (i.e., $d_A(c, c_r) < d_A(c, c_l)$). If a vote v coincides with the axis A then clearly exactly $min(d_A(c, c_r), d_A(c, c_l)) = d_A(c, c_r)$ swaps are needed to make c the candidate who gets vetoed in v.

If v does not coincide with A, we have to distinguish three cases. First, let c be the peak of v. In this case it is clear that c has to be swapped with all other candidates to get vetoed and thus we need exactly $d_A(c,c_r)+d_A(c,c_l) \geq min(d_A(c,c_r),d_A(c,c_l))$ swaps. Second, let c be left from v's peak on axis A. This means that, according to the definition of single-peakedness, all the candidates left from c on axis A are ranked lower than c in v. To swap c through to the last position, we will have to make at least $d_A(c,c_l) > min(d_A(c,c_r),d_A(c,c_l))$ swaps. Finally, let c be right from v's peak on axis A. This means that all the candidates on axis A right from c are ranked lower than c in v. To swap c through to the last position, we will have to make at least $d_A(c,c_r) = min(d_A(c,c_r),d_A(c,c_l))$ swaps. ❑

Using Lemma 5.5, the following two theorems can be shown.

Theorem 5.6. *Let k be a positive integer with $k \geq 2$.*

1. *Let the number of candidates be $m = 2k$. For each $\ell \geq 0$,* VETO-ℓ-GLOBAL SWAPS-CCWM *is in* P *if $\ell \leq k^2-k-1$ and* NP*-complete otherwise.*
2. *Let the number of candidates be $m = 2k-1$. For each $\ell \geq 0$,* VETO-ℓ-GLOBAL SWAPS-CCWM *is in* P *if $\ell \leq k^2-2k$ and* NP*-complete otherwise.*

Proof. We only prove (1), the proof of (2) is similar. Let A be the axis for which the election is nearly single-peaked, and let c_l and c_r be the leftmost and rightmost candidates in A, respectively. In the $\ell \leq k^2-k-1$ case we again count the number of candidates who can be vetoed. These are the two candidates c_l and c_r, and the maximal number of candidates who can be "swapped" to the last position with at most ℓ swaps. We can make at most $k^2-k-1 = -1+2\sum_{i=0}^{k-1} i$ swaps and consequently at most $m-1$ different candidates can be swapped to a last position in some vote (cf. Lemma 5.5). Note that with exactly k^2-k global swaps we could push every candidate (including c_l and c_r) to the last position in at least one vote. Thus, there is at least one candidate who never gets vetoed. Hence, manipulation is only possible if the distinguished candidate is amongst the candidates who never get vetoed by the nonmanipulators.

To show hardness we reduce from PARTITION. Let $\ell \geq k^2-k$. Given a multiset $S = \{k_1,\ldots,k_s\}$ of s integers that sum to $2K$, define the following instance of VETO-ℓ-GLOBAL SWAPS-CCWM. Let $C = \{p,c_l,c_r,c_1,\ldots,c_{m-3}\}$ be the set of candidates and let p be the distinguished candidate. Let A be the axis for which the election is nearly single-peaked and let candidates c_l and c_r be the leftmost and rightmost candidates in A. Let the nonmanipulative voters consist of $m-2$ voters, each with weight K such that for every candidate $c \in C \setminus \{c_l,c_r\}$ there is a nonmanipulative voter who ranks c last but otherwise the votes are identical with the axis A or its reverse $\overline{A}$ (depending on to which extreme c is closer in A). Note that in this case we need k^2-k global swaps to make the profile single-peaked which is still less or equal ℓ. Let $\mathscr{L}$ consist of s manipulators with weights $k_1,\ldots,k_s$.

We claim that there is a subset $S' \subset S$ such that the elements in S' sum to K if and only if p can be made a winner of the election by constructive coalitional weighted manipulation.

"$\Rightarrow$": Suppose there is a subset $S' \subset S$ such that the elements in S' sum to K. Let all the manipulators whose weight is in S' vote identically to the axis A, and all the manipulators whose weight is in $S \setminus S'$ vote reverse. It is easy to see that now all candidates tie for first place thus, the distinguished candidate p is a winner.

"$\Leftarrow$": Suppose that p can be made a winner of the election by constructive coalitional weighted manipulation. Note that p ties (with $c_1,\dots,c_{m-3}$) for the third place K points behind both candidates c_l and c_r. The only way p can gain K points on these two candidates is if the manipulators can be divided into two groups, both weighting K points and vetoing candidates c_l and c_r, respectively. Thus, there is a subset $S' \subset S$ such that the elements in S' sum to K. ❑

We omit the hardness proof of the following theorem because it is identical to the previous proof.

Theorem 5.7. *Let $m \geq 3$ denote the number of candidates. For each $\ell \geq 0$,* VETO-ℓ-LOCAL SWAPS-CCWM *is in* P *if $\ell \leq \lfloor \frac{m-1}{2} \rfloor - 1$ and* NP*-complete otherwise.*

Proof. Let A be the axis along the election is nearly single-peaked, and let c_l and c_r be the leftmost and rightmost candidates in A, respectively. In the $\ell \leq \lfloor \frac{m-1}{2} \rfloor - 1$ case we again count the number of candidates who can be vetoed. These are the two candidates c_l and c_r, and all the candidates who can be "swapped" to the last position with at most ℓ swaps in each vote. From Lemma 5.5 follows that there is at least one candidate who never gets vetoed. Hence, manipulation is only possible if the distinguished candidate is among the candidates who never gets vetoed by the nonmanipulators.

The hardness proof is identical to the proof of Theorem 5.6. ❑

Theorem 5.8. *Let $m \geq 3$ be the number of candidates in an election E. For each $\ell \geq 1$,* VETO-ℓ-CANDIDATE PARTITION-CCWM *is in* P *if $\ell \leq \lfloor \frac{m-1}{2} \rfloor$ and* NP*-complete otherwise.*

Proof. In the $\ell \leq \lfloor \frac{m-1}{2} \rfloor$ case we again count the number of candidates who can be vetoed. Since we have ℓ single-peaked partitions, there can be at most 2ℓ different candidates being vetoed. Since $2\ell < m$, there has to be at least one candidate who never got vetoed. Thus, constructive coalitional weighted manipulation is only possible if the distinguished candidate is amongst the candidates who never got vetoed by the nonmanipulators.

To show hardness in the other case, we reduce from PARTITION. Let $\ell > \lfloor \frac{m-1}{2} \rfloor$. Given a multiset $S = \{k_1,\dots,k_s\}$ of s integers that sum to $2K$, define the following instance of VETO-ℓ-CANDIDATE PARTITION-CCWM. Let $C = \{p,a,b,c_1,\dots,c_{m-3}\}$ be the set of candidates and let p be the distinguished candidate. Let the nonmanipulative voters consist of $m-2$ voters, each with weight K such that for every candidate $c \in C \setminus \{a,b\}$ there is a nonmanipulative voter who ranks c last. Note that in this case we need $\lceil \frac{m-2}{2} \rceil$ different axes (or candidate partitions). Since $\lceil \frac{m-2}{2} \rceil = \lfloor \frac{m-1}{2} \rfloor < \ell$, there is at least one axis (partition) left over we have not used yet. Let $\mathscr{L}$ consist of s manipulators with weights $k_1,\dots,k_s$.

We claim that there is a subset $S' \subset S$ such that the elements in S' sum to K if and only if p can be made a winner of the election by constructive coalitional weighted manipulation.

"$\Rightarrow$": Suppose there is a subset $S' \subset S$ such that the elements in S' sum to K. Let all the manipulators whose weight is in S' vote $a(C \setminus \{a,b\})b$, and all the manipulators whose weight is in $S \setminus S'$ vote reverse, $b\overline{(C \setminus \{a,b\})}a$. It is easy to see that now all candidates tie for first place thus, the distinguished candidate p is a winner.

"$\Leftarrow$": Suppose that p can be made a winner of the election by constructive coalitional weighted manipulation. Note that p ties for third place K points behind both candidates a and b. The only way p can gain K points on these two candidates is if the manipulators can be divided into two groups, both weighting K points. The first group vetoes a, the second group vetoes b. Thus, there is a subset $S' \subset S$ such that the elements in S' sum to K. ❑

Finally, we turn to VETO-ℓ-ADDITIONAL AXES-CCWM.

Theorem 5.9. *Let* $m \geq 3$. *For each* $\ell \geq 0$, VETO-ℓ-ADDITIONAL AXES-CCWM *is in* P *if* $\ell \leq \lfloor \frac{m-1}{2} \rfloor - 1$ *and* NP-*complete otherwise.*

Proof. The same proof holds as for the candidate partition case. The -1 in the bound on ℓ comes from the fact that ℓ *additional* axes give us $\ell + 1$ axes in total. ❑

6 Conclusions and Open Questions

We have investigated the nearly single-peaked consistency problem. To this end, we have formally defined two notions of nearly single-peakedness suggested by Escoffier, Lang, and Öztürk [ELÖ08]. Furthermore, we have introduced three new notions of nearly single-peakedness. We have drawn a complete picture of the relations between all the notions of nearly single-peakedness discussed in this paper. For five notions we have shown that deciding single-peaked consistency is NP-complete and for k-candidate deletion we have presented a polynomial time algorithm. An obvious direction for future work is to pinpoint the complexity of CANDIDATE PARTITION SINGLE-PEAKED CONSISTENCY.

NP-completeness, however, does not rule out the possibility of algorithms that perform well in practice. One approach is to search for fixed-parameter algorithms, i.e., an algorithm with runtime $f(k) \cdot poly(n)$ for some computable function f. A fixed-parameter algorithm for MAVERICK SINGLE-PEAKED CONSISTENCY has been presented by Bredereck [Bre12]. The design of fixed-parameter algorithm for nearly single-peaked consistency deserves further attention. A second approach is the development of approximation algorithms since nearly single-peaked consistency can also be seen as an optimization problem.

We have studied the complexity of manipulation in nearly single-peaked elections. The analysis of manipulation and control in such elections has already been started in [FHH11] for some distance measures. This work has yet to be extended to the distance measures introduced in this paper. Finally, there might be further useful and natural distance measures regarding single-peakedness to be found, e.g. combinations of measures presented in this paper.

Acknowledgments

We thank the anonymous COMSOC-2012 referees for their very helpful comments and suggestions.

References

[BBHH10] F. Brandt, M. Brill, E. Hemaspaandra, and L. A. Hemaspaandra. Bypassing combinatorial protections: Polynomial-time algorithms for single-peaked electorates. In *Proceedings of the 24th AAAI Conference on Artificial Intelligence (AAAI-10)*, pages 715–722. AAAI Press, 2010.

[BCE12] F. Brandt, V. Conitzer, and U. Endriss. Computational social choice. In G. Weiss, editor, *Multiagent Systems*. MIT Press, 2012.

[BEH$^+$10] D. Baumeister, G. Erdélyi, E. Hemaspaandra, L. Hemaspaandra, and J. Rothe. Computational aspects of approval voting. In J. Laslier and R. Sanver, editors, *Handbook on Approval Voting*, chapter 10, pages 199–251. Springer, 2010.

[BH11] Miguel A. Ballester and Guillaume Haeringer. A characterization of the single-peaked domain. *Social Choice and Welfare*, 36(2):305–322, 2011.

[Bla48] D. Black. On the rationale of group decision making. *Journal of Political Economy*, 56(1):23–34, 1948.

[Bre12] R. Bredereck, 2012. Personal communication.

[BT86] J. Bartholdi and M. Trick. Stable matching with preferences derived from a psychological model. *Operations Research Letters*, 5(4):165 – 169, 1986.

[BTT89a] J. Bartholdi, C. Tovey, and M. Trick. The computational difficulty of manipulating an election. *Social Choice and Welfare*, 6(3):227–241, 1989.

[BTT89b] J. Bartholdi, C. Tovey, and M. Trick. Voting schemes for which it can be difficult to tell who won the election. *Social Choice and Welfare*, 6(2):157–165, 1989.

[BTT92] J. Bartholdi, C. Tovey, and M. Trick. How hard is it to control an election? *Mathematical and Computer Modeling*, 16(8/9):27–40, 1992.

[CGS12] Denis Cornaz, Lucie Galand, and Olivier Spanjaard. Bounded single-peaked width and proportional representation. In *Proceedings of the 20th European Conference on Artificial Intelligence (ECAI 2012)*, volume 242 of *Frontiers in Artificial Intelligence and Applications*, pages 270–275. IOS Press, 2012.

[Con09] V. Conitzer. Eliciting single-peaked preferences using comparison queries. *Journal of Artificial Intelligence Research*, 35:161–191, 2009.

[CSL07] V. Conitzer, T. Sandholm, and J. Lang. When are elections with few candidates hard to manipulate? *Journal of the ACM*, 54(3):Article 14, 2007.

[DKNS01] C. Dwork, R. Kumar, M. Naor, and D. Sivakumar. Rank aggregation methods for the web. In *Proceedings of the 10th International World Wide Web Conference*, pages 613–622. ACM Press, 2001.

[EFS09] E. Elkind, P. Faliszewski, and A. M. Slinko. Swap bribery. In *Proceedings of the 2nd International Symposium on Algorithmic Game Theory (SAGT-2009)*, pages 299–310, 2009.

[EFS12] E. Elkind, P. Faliszewski, and A. M. Slinko. Clone structures in voters' preferences. In *Proceedings of the 13th ACM Conference on Electronic Commerce (EC-12)*, pages 496–513. ACM, 2012.

[ELÖ08] B. Escoffier, J. Lang, and M. Öztürk. Single-peaked consistency and its complexity. In *Proceedings of the 18th European Conference on Artificial Intelligence (ECAI 2008)*, volume 178 of *Frontiers in Artificial Intelligence and Applications*, pages 366–370. IOS Press, 2008.

[ELP12] G. Erdélyi, M. Lackner, and A. Pfandler. The complexity of nearly single-peaked consistency. In F. Brandt and P. Faliszewski, editors, *Proceedings of the 4th International Workshop on Computational Social Choice*, pages 179–190, September 2012.

[ER97] E. Ephrati and J. Rosenschein. A heuristic technique for multi-agent planning. *Annals of Mathematics and Artificial Intelligence*, 20(1–4):13–67, 1997.

[FHH09] P. Faliszewski, E. Hemaspaandra, and L. A. Hemaspaandra. How hard is bribery in elections? *Journal of Artificial Intelligence Research*, 35:485–532, 2009.

[FHH10] P. Faliszewski, E. Hemaspaandra, and L. A. Hemaspaandra. Using complexity to protect elections. *Communications of the ACM*, 53(11):74–82, 2010.

[FHH11] P. Faliszewski, E. Hemaspaandra, and L. A. Hemaspaandra. The complexity of manipulative attacks in nearly single-peaked electorates. In *Proceedings of the 13th Conference on Theoretical Aspects of Rationality and Knowledge (TARK-2011)*, pages 228–237, 2011. Full version available as Technical Report arXiv:1105.5032v2 [cs.GT], ACM Computing Research Repository (CoRR), July 2012.

[FHHR11] P. Faliszewski, E. Hemaspaandra, L. A. Hemaspaandra, and J. Rothe. The shield that never was: Societies with single-peaked preferences are more open to manipulation and control. *Information and Computation*, 209(2):89–107, 2011.

[FL97] M. Frances and A. Litman. On covering problems of codes. *Theory of Computing Systems*, 30:113–119, 1997.

[FP10] P. Faliszewski and A. D. Procaccia. AI's war on manipulation: Are we winning? *AI Magazine*, 31(4):53–64, 2010.

[GJ79] M. Garey and D. Johnson. *Computers and Intractability: A Guide to the Theory of NP-Completeness*. W. H. Freeman and Company, 1979.

[GMHS99] S. Ghosh, M. Mundhe, K. Hernandez, and S. Sen. Voting for movies: The anatomy of recommender systems. In *Proceedings of the 3rd Annual Conference on Autonomous Agents*, pages 434–435. ACM Press, 1999.

[MN08] T. Meskanen and H. Nurmi. Closeness counts in social choice. In M. Braham and F. Steffen, editors, *Power, Freedom, and Voting*, pages 289–306. Springer, 2008.

[Wal07] T. Walsh. Uncertainty in preference elicitation and aggregation. In *Proceedings of the 22nd AAAI Conference on Artificial Intelligence (AAAI-07)*, pages 3–8. AAAI Press, 2007.